

REPUBLIC OF PERU

REPORT ON GEOLOGICAL SURVEY


OF

ISCAYCRUZ (OYON) AREA

PHASE I

MAY 1984

JAPAN INTERNATIONAL COOPERATION AGENCY METAL MINING AGENCY OF JAPAN



REPUBLIC OF PERU

REPORT ON GEOLOGICAL SURVEY

OF

ISCAYCRUZ (OYON) AREA

PHASE I

MAY 1984

JAPAN INTERNATIONAL COOPERATION AGENCY METAL MINING AGENCY OF JAPAN

PREFACE

The Government of Japan, in response to the request of the Government of the Republic of Peru, decided to conduct collaborative mineral exploration, that is drilling and tunnelling surveys, in the Iscaycruz (Oyon) area and entrusted its execution to Japan Internatinal Cooperation Agency (JICA) and Metal Mining Agency of Japan (MMAJ).

Metal Mining Agency of Japan dispatched a survey team headed by Mr. Jinichi Nakamura to conduct the Phase II of the project. The survey had been started on 22 June, 1983 following the Phase I survey and accomplished on 12 March, 1984 under close cooperation with the Government of the Republic of Peru and its various authorities.

This report is a compilation of the survey of the Phase II, and after the completion of the project the consolidated report will be submitted to the Government of the Republic of Peru.

We wish to express our appreciation to all of the organizations and members who bore the responsibility for the project, the Government of the Republic of Peru, Instituto Geologico, Minero y Metalurgico, and other authorities and the Embassy of Japan in Peru.


April 1984

Keisnhe Acita

Keisuke Arita President Japan International Cooperation Agency

Masayuki Mishice

Masayuki Nishiie President Metal Mining Agency of Japan



ABSTRACT

This report summarizes results of the second year's work of the Cooperative Basic Geological Survey for Development of Mineral Resources carried out in the Iscaycruz Area, the Republic of Peru.

The purpose of this project is to examine relationship between geological structure and mineralization, and to confirm lateral and vertical continuity of the mineralized zone, by means of drilling exploration and tunnelling exploration in this area.

The Iscaycruz Area had been extracted as a favorable area where economic ore deposits would be expected to be emplaced, by the results of the Cooperative Basic Geological Survey for Development of Mineral Resources in the Oyon Area, which was carried out during the period of three years from 1979 to 1981.

The Iscaycruz Area is located about 150 km north of Lima, in the backbone range of the West Andes. Geologically, Mesozoic sedimentary rocks are widely distributed in this area, forming remarkable composit folded structure due to tight forlding with the axes in the Andean direction, namely NNW-SSE.

The Iscaycruz mineralized zone is located approximately 7 km south-southeast of Oyon, in the high mountain at the altitude of 4,700 m above sea level. The mineralization occurs in the limestones of the Santa Formation, about 50 to 100 meters in thickness, and continues about 12 km along the strike. In this mineralized zone, ore deposits are divided roughly into two categories; the one is contact metasomatic skarn type ore deposits represented by copper-zinc skarn orebodies and the other is hydrothermal replacement ore deposits represented by copper-lead-zinc massive sulphide orebodies as well as by disseminated orebodies of lead and zinc in the siderite beds.

The investigations in the present year, following the works in the last year, the tunnelling exploration (Adit-N main tunnel, Adit-N crosscut, Adit-S main tunnel, total excavation length 680 m) and the underground diamond drilling (2 drill sites, 4 holes, total drill length 910 m) were carried out in the Limpe area in the central part of the Iscaycruz mineralization zone, where the emplacement of high grade copper-lead-zinc massive sulphide ore deposits would be expected most favorably in the Iscaycruz mineralization zone.

By the results of the tunnelling exploration, both main tunnels of Adit-N (4,690 meters above sea level) and Adit-S (4,570 meters above sea level) are located in quartzite of the Chimu Formation. The Santa Formation is recognized over 80 meters along the crosscut of the Adit-N and, in addition to the intense mineralization mainly of pyrite, indications of high grade zinc mineralization of Zn 17.13% in average of the true width of 12 meters are confirmed on the horizon of the hanging-wall-side orebody.

By the results of the underground diamond drilling, heavy pyrite mineralization was recognized in 4 holes respectively. By the drill hole IC--6, which was located in the north of the crosscut of the Adit-N, indications of high grade zinc mineralization (core length 7.0 m, Cu 0.32%, Zn 21.59%) and copper disseminations in pyrite mass (core length 7.8 m, Cu 2.48%, Zn 0.46%) were recognized in the peripheral zone of the massive pyrite orebody along the horizon of the footwall-side orebody. And it has been clarified that there would be intimate relation between the pyrite mineralization and the copper-lead-zinc mineralization.

INTEGRATED CONTENTS

PREFACE

INDEX MAP (FIG. 1)

ABSTRACT

GENERAL REMARKS

Chapter	1	Introduction	1
Chapter	2	Outline of the Surveyed Area	4
Chapter	3	Outline of the Survey Results	8
Chapter	4	Conclusion and Recommendation	12

PARTICULARS


Part I	Drilling Exploration I-1
Part II	Tunnelling Exploration II-1

APPENDICES

Data of Drilling Data of Tunnelling Geological Data

ATTACHED PLATES

Maps of Drilling Maps of Tunnelling



GENERAL REMARKS CONTENTS

•

CHAPTER 1	INTRODUCTION 1	l
1-1	Purpose of the Survey 1	ĺ
1-2	Circumstances of the Survey I	í
1-3	Outline of the Survey	(
1-4	Organization of the Survey Team 2	2
CHAPTER 2	OUTLINE OF THE SURVEYED AREA 4	ł
2-1	The Surveyed Area 4	ł
2–2	Outline of Geology 4	ŀ
2-3	Outline of Ore Deposits	5
CHAPTER 3	OUTLINE OF THE SURVEY RESULTS	3
3-1	Drilling Exploration 8	3
3-2	Tunnelling Exploration	9
CHAPTER 4	CONCLUSION AND RECOMMENDATION 12	2
4-1	Conclusion	2
42	Recommendation	2
REFERENCES	5 14	1

LIST OF FIGURES

Fig.	1		Index Map
Fig.	2	•	Location Map of the Surveyed Area
Fig.	3		Schematic Profile of the Central Andes Area
Fig.	4		Geological Map of the Iscaycruz Area
Fig.	5		Exploration Map of the Limpe Area
Fig.	6		Summarized Projective Section of the Exploration Results in the Limpe Area

v

, **e**

۳

.

•

LIST OF PLATES

PL. 1	Exploration Map of the Limpe Area	
	Showing the Drilling and Tunnelling Sites	1 = 2,000
PL. 2	Summarized Projective Map of the Drilling Results	1 = 2,000
PL. 3	Summarized Projective Section of the Drilling Results	1 = 2,000
PL. 4	Inferred Geological Map on 4,690 m and 4,570 m Levels	1 = 2,000
PL. I6	Geologic Drill Log, IC–6	1 = 200
PL. I-7	Geologic Drill Log, IC-7	1 = 200
PL. I8	Geologic Drill Log, IC-8	1 = 200
PL. I-9	Geologic Drill Log, IC–9	1 = 200
PL. II-1-1	Surveying Map of Exploration Tunnel, Adit-N	1 = 500
PL. II-1-2	Surveying Map of Exploration Tunnel, Adit-S (1)	1 = 500
PL. II-1-3	Surveying Map of Exploration Tunnel, Adit-S (2)	1 = 500
PL. II-2-1	Surveying Map Showing Location and Level of	
	Exploration Tunnel, Adit-N	1 = 1,000
PL. II-2-2	Surveying Map Showing Location and Level of	
	Exploration Tunnel, Adit-S	1 = 1,000
PL. II-3-3	Geological Sketch, Adit-N (3)	1 = 200
PL. II-3-4	Geological Sketch, Adit-N (4)	1 = 200
PL. II-3-5	Geological Sketch, Adit-N (5)	1 = 200
PL. II-4-2	Geological Sketch, Adit-S (2)	1 = 200
PL. II-4-3	Geological Sketch, Adit-S (3)	1 = 200
PL. II-4-4	Geological Sketch, Adit-S (4)	1 = 200

,

CHAPTER 1 INTRODUCTION

1--1 Purpose of the Survey

The purpose of this survey is, in addition to the comprehension of the geological structure in relation to the mineralization in the Iscaycruz Area, to confirm lateral and vertical continuity of the mineralized zone, by means of drilling and tunnelling explorations and the analysis of the related geology.

The survey works have been completed with the cooperation of the Instituto Geologico, Minero y Metalurgico (INGEMMET).

1-2 Circumstances of the Survey

Cooperative Basic Geological Survey for the Development of the Mineral Resources was carried out for three years from 1979 to 1981 in the Oyon Area (860 km²) including the Iscaycruz Area (40 km²). In addition to geological mapping, geochemical survey and detailed geological survey, the following investigations were carried out in the Iscaycruz Area; geophysical prospecting by IP method (15 survey lines, total length 35.9 km); geophysical prospecting by EM method (10 survey lines, total length 13.0 km); diamond drilling (12 holes at 11 sites, total length 2,654 m).

By the results of these investigations, it was confirmed that the high grade copper-lead-zinc sulphide ore deposits and skarn ore deposits were emplaced in the Iscaycruz Area and also it was proved that high potentiality of the mineralization would be expected in this area for the development of mineral resources.

On the basis of the above results obtained through the Cooperative Basic Geological Survey in the Oyon Area, more detailed investigations by drilling and tunnelling explorations were recommended in Limpe area and in Tinyag area, where the most high grade lead-zinc ore deposits in the Iscaycruz Area were expected.

The Cooperative Basic Geological Survey for the Development of Mineral Resources in the Iscaycruz Area was scheduled to be carried out in three years' program on the basis of the Scope of Work signatured on May 11, 1982 between the Instituto Geologico, Minero y Metalurgico and the Metal Mining Agency of Japan. This year survey (1983) is the second year plan (Phase II).

1-3 Outline of the Survey

1) Drilling Exploration

In this year, underground drilling of 4 holes at 2 sites, 310 m point of Adit-N and 270 m

point of Adit-S, was carried out (refer to Fig. 5).

2) Tunnelling Exploration

The purpose of the Tunnelling exploration is to confirm, along the tunnel wall passing through the orebodies, various factors as figures of orebodies, features and continuity of grade distribution and aspect of combinations of ore minerals, as well as to utilize the tunnel as the base for the underground drilling crosscutting the orebodies, which is the most effective for the confirmation of lateral and vertical continuity of the orebodies and the mineralized zone (refer to Fig. 5).

As the excavation and the maintenance of the tunnels were supposed to be difficult according to the results of the diamond drilling which revealed that the walls would be soft and weak in the mineralized zone, the main tunnel was excavated in the hard rock of quartzite of the Chimu Formation, from which the crosscut tunnels into the mineralized zone and underground drill chambers will be excavated.

As the time for the investigation was limited, two starting points were established for the excavation of the tunnels with the approximate distance of 1,400 m, so that the two faces, that are Adit-N and Adit-S, could be worked at the same time.

The length of tunnels excavated in the first year and this year is as follows:

	Phase I	Phase II	Total
Adit-N	310	200	510
Adit-N, Crosscut		150	150
Adit-S	270	330	600
Total	580	680	1,260

1-4 Organization of the Survey Team

Japan Side Planning, Negotiation, and Supervision							
Makoto Ishida	MMAJ*						
Zenji Kita	MMAJ						
Hideyuki Ueda	MMAJ						
Peru side Planning and Negotiation							
Francisco Sotillo	INGEMMET**						
Gregorio Flores	INGEMMET						
Augusto Zelaya	INGEMMET						
Japanese Survey Team							
Jinichi Nakamura (Team Leader)	MINDECOX						

(Leader of Drilling)	MINDECO
(Drilling)	,,
"	77
"	"
(Leader of Tunnelling)	17
(Tunnelling)	35
(Team Leader)	INGEMMET
(Investigation)	53
**	**
	(Drilling) , , (Leader of Tunnelling) (Tunnelling) (Team Leader) (Investigation)

* Metal Mining Agency of Japan

.

,

-

- **Instituto Geologico, Minero y Metalurgico
- x Mitsui Mineral Development Engineering Co., Ltd.

٠

CHAPTER 2 OUTLINE OF THE SURVEYED AREA

2-1 The Surveyed Area

The Iscaycruz Area is, on the administrative division, belonging to Provincia Cajatambo of Departamento Lima, and is located about 150 km north of Lima, the capital (see Fig. 1).

To reach the Area from Lima, it is necessary to come to Sayan through Chancay (137 km, about 3 hours by vehicle). From Sayan, running along a rough and bending road along the valley of the Rio Huaura, one can come to Oyon through Churin (93 km, about 3 hours). After passing through Pampahuay, an access road is available to pass over the range at the approximate altitude of 5,000 meters above sea level, to come to the Iscaycruz Area (approximately 30 km, about 2 hours, (see Fig. 2).

The surveyed area lies in the Cordillera Occidental, a main range of the Western Andes, and is situated in the source area of Rio Huaura which belongs to the drainage system of the Pacific coast, about 11 km west to the continental divide. The area forms steep mountaneous topographical feature. The elevation of the surveyed area is $4,600 \sim 4,700$ meters above sea level.

The climate in this area belongs to what is called Andean highland climate. Daily variation of temperature is in fairly great range, and sometimes the temperature reaches over 20° C in daytime, while it goes down to less than 0° C in night time. To take annual variation of the climate, there are two seasons. The dry season is in the period from May to September, while the wet season is in the period from October to April. In the wet season, snowfall can be seen almost every day in the highland area at the altitude of more than 4,000 meters above sea level.

2–2 Outline of Geology

1) Regional Geological Setting

The Iscaycruz Area and the peripheral area belong stratigraphically to the zone of Cretaceous sedimentary basin (la Zona de la Cuenca Cretacea) by Cobbing (1973), and is structually situated in the folding-thrusting zone (la Zona de Pliegues y Sobreescurrimientos) by Wilson (1967).

Thick Cretaceous sedimentary rocks are widely distributed in this area. The lower part is composed mainly of clastic rocks such as siliceous sandstone and shale, and the upper part calcareous rocks associated with dolostone and shale, and the uppermost part red formation.

The clastic rocks of the lower part is divided into the Oyon, Chimu, Santa, Carhuaz and Farrat Formations, and the calcareous rocks of the upper part into the Pariahuanca, Chulec,

Pariatambo, Jumasha, Celendin and the uppermost red Casapalca Formations in ascending order. These formations are unconformably covered by the Calipuy volcanics in Tertiary and are intruded by tonalites, dacites, granite porphyry and others (refer to Fig. 3 and Fig. 4).

The Cretaceous sedimentary rocks suffered intensely a structural movement in consequency of the Andean Orogeny to form composite folds with NNW-SSE trend. Anticlines and synclines appear at intervals of 2 to 3 km, sometimes several tens meters, so that the same stratum is repeatedly exposed at the surface. At the central part in the orogenic zone thrust faults parallel to the fold axis are developed.

On the east of this area the Eastern Andes consisting mainly of Paleozoic sedimentary rocks and Pre-Cambrian metamorphosed rocks runs, while on the west Tertiary volcanic rocks are continuously distributed and the Andean batholith intrudes into this volcanic rocks (refer to Fig. 3).

2) Outline of Geology in the Iscaycruz Area

The Iscaycruz Area is about 6 km to 18 km south-south-east of Oyon. Canaypata is at the north end of the area and Antapampa is at the south end (refer to Fig. 2).

In the east of this area, an anticline is recognized with the axis running in NNW-SSE direction. The Oyon Formation, the lowest Cretaceous, composed mainly of sandstone and shale with coal measures and the overlying Chimu Formation, 600 to 700 meters thick, composed of quartzite or quartzose sandstone are distributed along the axis of the anticline. They look dark grey to dark brown in color and form irregular rough mountain land. In the west of this area, a syncline is recognized with the axis in NNW-SSE direction, along which is distributed the upper Cretaceous Jumasha Formation composed of massive limestone of the thickness of almost 1,400 meters. The limestone forms steep mountain land, brightly shining in grey color. Between the two mountain lands, topographically lower part has been formed in the area occupied by the Carhuaz Formation composed of the alternation of shale and sandstone, 500 to 700 meters thick.

In a narrow zone between the Chimu Formation and the Carhuaz Formation, the Santa Formation is distributed. The Santa Formation is as thick as 50 to 100 meters, composed of wellstratified bluish grey limestones. This formation constitutes the country rock of the mineralization in the Iscaycruz Area. Between the Carhuaz Formation and the Jumasha Formation, there are four other formations which are distributed zonally. They are Farrat Formation, about 100 meters in thickness, composed of quartzose sandstone and calcareous sandstone; Pariahuanca Formation, about 100 meters in thickness, composed of dark grey massive limestone; Chulec Formation, about 200 meters in thickness, composed of the alternation of thin layers of shale and dark grey to dark-colored limestone.

The Santa Formation is situated on the wing of the fold structure. The dipping of the strata of this formation is almost vertical, as they constitute parts of the remarkable tight-folds. Overturned structures are observed to be developed in the Limpe area and Tinyag area in the central part of this area.

As for igneous rocks, dacitic porphyry is recognized near the axis of the syncline in the west of Cumbre de Iscaycruz (Iscaycruz pass) and also acidic dyke complex is found to have been active around the anticline axis near Cumbre de Cunsha Punta, in the middle to southern part of this area.

2-3 Outline of Ore Deposits

1) Outline

According to Bellido et al (1972), the Iscaycruz Area is located geologically in the Sub-Provincia Polimetalica del Altiplano in the Provincia Metalogenica Andina Occidental. In the vicinity of the survey area, there are many silver-lead-zinc mines in operation, such as Raura mine (Pb · Zn), Uchucchacua mine (Ag), Atacocha mine (Pb · Zn · Ag), Cerro de Pasco mine (Pb · Zn · Ag), Huaron mine (Pb · Zn · Ag), and Santander mine (Cu · Zn).

2) Iscaycruz Mineralized Zone

The Iscaycruz Mineralized zone is found in the limestone of the Santa Formation, and is distributed intermittently along the limestone in a distance of about 12 km from Canaypata, the northern end, to Antapama, the southern end. The indications of mineralization are found as dark-colored gossans bearing lead and zinc, massive pyrite orebodies associated with galena and sphalerite, skarn masses containing chalcopyrite and sphalerite, hematite masses disseminated with chalcopyrite and sphalerite, and disseminations in dolostones with galena and sphalerite (see Fig. 4).

Dark-colored gossans exposed widely on the surface are composed mainly of goethite, quartz and kaolinite, associated with manganese oxides and siderite. Most of the metal ingredients in the gossans are thought to be in the form of oxide or carbonate such as chalcophanite and smithsonite. It is inferred that the dark-colored gossans are the oxidation products of manganiferrous siderite.

Massive pyrite ore deposit, which is composed mainly of pyrite associated with pyrrhotite and marcasite, is occasionally enriched with galena and sphalerite. There occurs a lot of druses in pyrite orebody and hematite in the marginal places. In sphalerite, spotted small grains of chalcopyrite are contained. Main ore minerals of skarn ore deposit are chalcopyrite, sphalerite, pyrite, and magnetite, and main skarn minerals are tremolite, garnet, epidote, and quartz.


Silicification, sericitization, argillization, sideritization, dolomitization, and brecciation are remarkable alterations in the host rock of the ore deposits. The acidic dykes, which intruded into the Oyon and Chimu Formations around Cumbre de Cunsha Punta, are thought to have been related to the mineralization.

As for the fracture system, shear faults of WNW-ESE and NNE-SSW directions, both of which are oblique to the folding axis, tension fracture of ENE-WSW which shows right angle to the folding axis, and thrust fault and bedding fracture parallel to the folding axis are observed to be developed in this area.

The mineralized zone in the Iscaycruz Area is in a narrow zone about 12 km in length. The exposures of the mineral indications are intermittent and the features of concentration of the ore minerals are variable. Viewing the whole area at a glance, the skarn ore deposits containing copper and zinc minerals are recognized in the Tinyag area, nearest to the center of the activity of the acidic igneous rocks. It is thought these skarn ore deposits would occupy the area corresponding to the central portion of the mineralization in this area. Both in the Limpe area in the north of this central area, and the Cunsha Punta area in the south of it, massive sulphide ore deposits have been found, in places associated with lead and zinc minerals. In the outermost zone of the Cumbre de Iscaycruz area and the Antapampa area, dissemination type ore deposits of lead and zinc in the manganiferrous siderite layers are recognized. These ore deposits of various types are distributed in zonal arrangement, centered in the acidic igenous rocks, and they are thought to have been formed in a single mineralosphere by a series of mineralization as a whole.



Fig. 2 Location and Access Map



.

.

Fig. 3. Schematic Profile of the Central Andes Area




Fig.4 Geological Map of the Iscaycruz Area

CHAPTER 3 OUTLINE OF THE EXPLORATION RESULTS

3–1 Drilling Exploration

In the present year, underground diamond drilling of 4 holes, whose total length was 910 meters, was carried out in two drill sites in the tunnels of Adit-N and Adit-S.

1) IC-6 and IC-7

In the Adit-N, drilling of the holes IC-6 and IC-7 was carried out at the point of 310 meters from the gate of the adit, which was corresponding to the midway between the surface drill holes of DDH-4 and IC-2.

In the drill hole IC-6, the purpose of which was to investigate details of the massive pyrite orebody in the lowest part of the Santa Formation in contact with the Chimu Formation as well as to explore lower extention of the hanging wall-side zinc orebody caught by the drill hole DDH-4, high grade zinc ores are confirmed to have been emplaced in the peripheral zone of the massive pyrite orebody and it has also been confirmed that the pyrite orebody would contain copper minerals in parts. The results of the analysis of the mineralized portions caught in this hole are given as follows.

Hole	Depth (m)	Length (m)	Number of Samples	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)
IC–6	108.0 - 115.0	7.0	5	15	0.32	0.02	21 59
IC–6	115.0 - 122.8	7.8	4	23	2.48	0.02	0.46
IC-6	122.8 - 145.0	22.2*	5	15	1.04	0.02	0.23
				* Core	Tecoverv	was noor	

Core recovery was poor.

In the hole IC-7, the purpose of which was to do exploration in the deep part $100 \sim 200$ m below the crosscut, pyrite orebody containing pyrrhotite was caught in the deep part below the foot-wall-side pyrite orebody and the hanging-wall-side zinc orebody.

2) IC-8 and IC-9

In the Adit-S, drilling of the holes IC-8 and IC-9 was carried out in the same bearing, at the point of 270 meters from the gate of the adit, for the purpose of the exploration for geological structure and mineralization in the area about 130 meters south of the surface drill hole IC-5. The target of the exploration by the drill hole IC-8 was at the level about 150 meters below surface while the target of the exploration by the hole IC-9 was at the level about 350 meters below surface.

By the results of the drilling of these two holes, it has been confirmed that the Santa Forma-

tion is as thick as 100 meters in this area, dipping 65° to the east, forming remarkable overturned structure, that the Santa Formation had been severely altered and mineralized, accompanying large scaled massive pyrite orebodies, and that copper minerals such as chalcopyrite and bornite are associated with hematite which is developed in the peripheral zone of the pyrite orebody. The results of the chemical analysis of the mineralized portions are shown as follows.

Hole	Depth (m)	Length (m)	Number of Samples	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)
IC8	159.2 - 163.8	4.6	1	40	2.59	0.02	0.30
IC8	174.5 — 178.1	3.6	3	23	2.43	0.11	0.11

3–2 Tunnelling Exploration

As the tunnelling exploration in this year, total 680 meters of tunnel excavation was carried out;

Adit-N (main tunnel)	200 m (cummulative total 510 m)
Crosscut of Adit-N	150 m
Adit-S (main tunnel)	330 m (cummulative total 600 m)

1) Adit-N (main tunnel)

Quartzite belonging to the Chimu Formation is recognized all along the adit. The strike of the quartzite is $N15^{\circ} \sim 20^{\circ}W$, and the dip is $80 \sim 85^{\circ}E$. Joints of WNW-ESE system are densely developed, which are almost rectangular to the bedding planes. At the point of 350 meters from the gate, fault fracture zone is recognized in the direction of NW-SE.

2) Crosscut of Adit-N

The crosscut of Adit-N was opened at the point of 310 meters from the gate in the main tunnel of the Adit-N. The location of this crosscut is in the midway of the surface drill holes of DDH-4 and IC-2. By the results of the excavation of this crosscut, remarkable indications of zinc mineralization have been confirmed in the true width of 12 meters.

To mention about the geology and the mineralization along the crosscut, the Chimu Formation composed mainly of quartzite is recognized to the 31 m point from the opening point, while the transitional zone of the Chimu Formation is found between 31 m point and the 70 m point from the opening point, comprising alternation of dolostone, shale, sandstone and quartzite.

The rocks of the Santa Formation are recognized in far side of the 70 m point. Within 9 meters of the width from the 70 m point to the 79 m point, alternation of marl and shale with the dissemination of sphalerite and pyrite is found, while, within 36 meters of the width from

the 79 m point to the 115 m point, massive pyrite orebody is recognized with the dissemination, in parts, of chalcopyrite. Alternation of limestone, shale and dolostone, not mineralized, is found within 22 meters of the width from the 115 m point to the 137 m point.

Within 12 meters of the width, indications of zinc mineralization are recognized, in which sphalerite is concentrated in dissemination in the matrix of pyritic mass. Continuous channel sampling with 1 meter interval along both walls was carried out and by the result of the chemical analysis, as shown below, the ore grade was as high as Zn 17.1% in average of 24 samples. This result has shown that the mineralization in this crosscut is superior in the points of size and grade, compared to the indication caught by the drill hole DDH-4 (width of indication 14.8 m, true width 7.4 m, Zn 14. 49%) which is located about 70 meters north of this crosscut, and to the indication caught by the drill hole IC-2 (width of indication 16.4 m, true width 7.0 m, Pb 4.43%, Zn 9.39%) located about 130 meters south of this crosscut.

	Length (m)	Number of Samples	Ag (g/t)	Cu (%)	ԲԵ (%)	Zn (%)
Right wall (north side)	12	12	11	0.11	0.10	17.11
Left wall (south side)	12	12	5	0.08	0.04	17.16
Average	12	24	8	0.10	0.07	17.13

In the far side of the 149 m point, remarkably fractured shale is recognized, and it is thought that the working face of the crosscut entered into the area where the rocks of the Carhuaz Formation are distributed.

By the excavation of this crosscut, it has been confirmed that gentle dipping faults are well developed in the direction of NW-SE, in addition to the steeply developed bedding plane faults of NNW-SSE system. The faults of NW-SE system are recognized at the 23 m point and at the 52 m point, where they are dipping $30^{\circ} \sim 40^{\circ}$ to the SW direction. It is estimated that dislocation of the beds is fairly large judging from the scale of the fractuation and the fault clay.

3) Adit-S

The Chimu Formation composed mainly of quartzite is recognized all along the Adit-S. The strike of the quartzite is N20°W, and the dip is $65^{\circ} \sim 70^{\circ}$ E, showing overturned structure. The quartzite is intensely silicified, and is massive, compact and hard, disseminated with pyrite. Joints of ENE-WSW system are remarkably developed. At the points of 319 m, 404 m and 500 m, respectively, faults of the ENE-WSW system are recognized. A fault zone composed of the faults of NNE-SSW system and those of ENE-WSW system is recognized between the 520 m point and the 537 m point. After passing this fault zone to the far side, alternation of marl, sandstone,

shale and quartzite is observed to appear instead of monolith of quartzite.

CHAPTER 4 CONCLUSION AND RECOMMENDATION

4–1 Conclusion

The investigation works carried out in the present year were those in the second phase of the three years program of the Cooperative Basic Geological Survey for Development of Mineral Resources in the Iscaycruz Area.

Following the first year's investigation, the tunnelling exploration of the Adit-N and the Adit-S was carried out, and in addition, crosscut tunnel was excavated as to the Adit-N. Furthermore, exploration by the underground diamond drilling was commenced in the tunnels of Adit-N and Adit-S.

Both of the main tunnels of Adit-N and Adit-S are situated in the quartzite of the Chimu Formation. However, by the excavation of the rocks of the Santa Formation over 80 meters along the crosscut of the Adit-N, extensive indication of zinc mineralization (true width 12 m, Zn 17.13%) has been confirmed associated with the massive pyrite orebody, in addition to the copper-disseminated massive pyrite orebody (width 36 m). This indication of zinc mineralization is correspondent to the extension of the hanging-wall-side orebody caught by the two surface drill holes located about 70 meters north and about 130 meters south of the area where the crosscut is located, but the size and the ore grade are superior to the indications caught by these surface drilling.

As to the results of the underground diamond drilling, indications of high grade zinc mineralization (core length 7.0 m, Cu 0.32%, Zn 21.59%) and indications of copper dissemination in pyrite mass (core length 7.8 m, Cu 2.48%, Zn 0.46%) are confirmed by the drill hole IC-6 in the peripheral zone of the massive pyrite orebody in the northern and deeper portion below the crosscut. Although fairly intense indications of pyrite mineralization have been confirmed in the holes of IC-7, IC-8 and IC-9, respectively, only a small scaled indication of copper mineralization has been caught by the drill hole IC-8.

4–2 Recommendation

It is desirable to carry out the investigations by tunnelling and underground diamond drilling continuously in the Limpe area, where indications of intense mineralization have been recognized and emplacement of high grade copper-lead-zinc ore deposits would be expected.

As to the Adit-N, because the foot-wall-side orebody, which is thought to be the most superior indication of the mineralization, has not been caught in the tunnel, it is recommended; to excavate second crosscut in the area where the foot-wall-side orebody is expected, for the purpose to confirm figure of the orebody, characteristics and continuity of the ore grade distribution and difference of the composition of ore minerals; to carry out underground diamond drilling for the purpose to clarify the conditions in the mineralized zones.

As to the Adit-S, it is recommended to keep excavating the main tunnel toward the rich ore shoot of the grade of lead and zinc 30%, which was caught by the surface drill hole DDH-5 located in the south of Cumbre de Limpe, and to excavate crosscut tunnel in this mineralized part for the purpose to confirm the condition of the mineralization. It is also recommended to open crosscut tunnels and to carry out underground diamond drilling in such areas as around the drill hold DDH-6, by which indications of high grade zinc mineralization were caught, and in and around an unexplored area between the drill holes IC-4 and IC-5.

Beyond the reach of the tunnelling exploration, it is desirable to carry out investigations by surface diamond drilling in the Tinyag area in the south, for the purpose to clarify the extent of high grade copper and zinc orebody which was caught by the surface drill hole DDH-7.





Fig. 5 Exploration Map of the Limpe Area



REFERENCES

Bellido, B.E. (1969) Sinopsis de la geologia del Peru. Serv. Geol. Min., Peru, Bel. 22.

Bellido, B.E., Luis de Montreuil, D. y Girard, P.D. (1956) Aspectos generales de la metalogenia del Peru. Serv. Geol. Min., Peru.

Cobbing, J. (1973)

Geologia de los cuadrangulos de Barranca, Ambar, Oyon, Huacho, Huaral y Canta. Ser. Geol. Min., Peru, Bol.26.

- Einaudi, M.T. (1977) Environment of ore deposition at Cerro de Pasco, Peru. Econ. Geol., v.72, p.893-924.
- Fukahori, Y., Aikawa, K. and Kawasaki, M. (1980) Geology and ore deposit of the Huanzala mine - Mineralogical Study (in Japanese). Min. Geol. Japan, v.30, p.103-118.
- Horita, A., Oikawa, J. and Tagami, Y. (1973) Geological features of the Huanzala ore deposits, Peru (in Japanese). Min. Geol. Japan, v.23, p.265-274.
- James, D.E. (1971) Plate tectonic model for the evolution of the Central Andes. Geol. Soc. Amer. Bull., v.82, p.3325-3346.
- Japan International Cooperation Agency and Metal Mining Agency of Japan (1980-1982), Report on geological survey of the Oyon area. Phase I., Phase II., Phase III.
- Japan International Cooperation Agency and Metal Mining Agency of Japan (1982), Consolidated report on geological survey of the Oyon area.

Japan International Cooperation Agency and Metal Mining Agency of Japan (1983), Report on geological survey of the Iscaycruz (Oyon) area. Phase I.

Jenks, W.F. (1956)

Peru, Handbook of South American Geology. Geol. Soc. Amer., Memoir, 65, p.215-247.

Jenks W.F. (1979)

Geology of South America, Geology of the World (in Japanese). Iwanami, Tokyo, p.143-172.

Miyashiro, A. (1979)

Orogenesis based on the plate tectonics, The Trasitional Earth (in Japanese). Iwanami, Tokyo, p.35-144.

Petersen, U. (1965)

Regional geology and major ore deposits of Central Peru. Econ. Geol., v.60, p.407-475.

Petersen, U. (1970)

Metalogenetic provinces of South America. Geol. Rundschau, v.59, p.834-897.

Sato, H. and Saito, N. (1977) Pyrite zones and zonal distribution of Cu-Pb-Zn ores in Huanzala mine, Peru (in Japanese). Min. Geol. Japan, v.27, p.133-144.

Wilson, J.J. (1963)

Cretaceous stratigraphy of Central Andes of Peru. Amer. Assoc. Petrol. Geol. Bull., v.47, p.1-34.

PARTICULARS PART I DRILLING EXPLORATION

PART I DRILLING EXPLORATION CONTENTS

Chapter 1		Drilling Exploration I-1		
	1-1	Outline of the Exploration I-1		
	1-2	Preparation		
	1–3 Drilling Operations I–2			
	1–4	1-4 Mobilization and Removal		
	15	Performance of DrillingI-7		
Chapter	2	Geology and Mineralization in the Drill Holes $\dots \dots \dots \dots \dots \dots \dots I-8$		
	2-1	IC-6 I-8		
	2-2	IC-7 I-9		
-	2-3	IC-8 I-10		
	2–4	IC9 I-11		

•

P

LIST OF FIGURES

Fig.	I 1	Progressive Record of Diamond Drilling, IC-6
Fig.	I-2	Progressive Record of Diamond Drilling, IC-7
Fig.	I-3	Progressive Record of Diamond Drilling, IC-8
Fig.	I4	Progressive Record of Diamond Drilling, IC-9
Fig.	1-5	Geological Section for IC-6
Fig.	I6	Geological Section for IC-7 and Crosscut
Fgi.	I—7	Geological Section for IC-8 and IC-9

,

٠

-

L'IST OF APPENDICES

- A. I-1 List of the Used Equipment for Drilling
- A. I-2 Articles of Consumption and Drilling Parts
- A. I-3 Preparation and Removal Records
- A. I-4 Operation Results of Drill Hole, IC-6
- A. 1-5 Operation Results of Drill Hole, IC-7
- A. I-6 Operation Results of Drill Hole, IC-8
- A. I-7 Operation Results of Drill Hole, IC-9
- A. I-8 Summarized Operational Data of Each Drill Hole
- A. I-9 Working Time of Each Drill Hole
- A. I-10 Drilling Meterage of Diamond Bits
- A. I-11 Specifications of Diamond Bits

Α.	III-1	Assay Results
А.	III-2	Summary of Microscopic Observations
Α.	111-3	Microscopic Observations of Polished Section
A.	III-4	Microphotograph
А.	III5	Summary of X-Ray Diffraction Analysis
A.	111–6	X-Ray Diffraction Chart

CHAPTER 1 DRILLING EXPLORATION

1–1 Outline of the Exploration

1) Drilling Exploration

The drilling exploration in the present year was carried out in the underground of Adit-N and Adit-S. The total length of the drill holes was 916.00 m, of 4 holes at two drill sites.

Tunnel	Hole	Direction	Inclination	Depth (m)	Core Length (m)	Core Rec. (%)
Adit-N	IC-6	280°	40°	200.30	165.10	82.4
Adit-N	IC-7	250°	-60°	242.80	201.40	82.9
Adit-S	IC-8	250°	30°	202.80	190.00	93.7
Adit-S	IC-9	250°	-80°	270.10	251.35	93.1
Tota	l			916.00	807.85	88.2

This drilling exploration in the underground was performed in the period of 134 days from September 20, 1983 to January 31, 1984.

The drill machine employed was TGM-3C (drilling capacity: NQ 510 m, BQ 660 m).

Location (grid coordinate) and altitude of each drill hole are as follows.

Tunnel	Hole	Longitude	Latitude	Elevation (m)
Adit-N	IC6	310,528E	808,854N	4,692
Adit-N	IC-7	310,528E	808,854N	4,692
Adit-S	IC-8	310,904E	808,112N	4,573
Adit-S	IC-9	310,904E	808,112N	4,573

2) Core Logging and Analysis

All the cores of the drill holes were logged with regard to lithology and mineralization. The results of the logging were described in the geological logs of the scale of 1 to 200.

As for the mineralized parts of the cores, half-split pieces or quarterly-split pieces were collected to prepare samples for chemical analysis, which was completed with various elements such as silver, copper, lead, and zinc.

Also, as to the parts of the cores where mineralization and indications of mineralization were recognized, polished sections were prepared for microscopic observation. Some of the samples were provided for the identification of minerals by X-ray diffraction analysis.

Main contents and number of the analyses are given as follows.

(1)	Chemical analysis of the mineralized parts of the cores (Ag, Cu, Pb, Zn)	00	samples
(2)	Microscopic observation of the polished sections of ores	10	pieces
(3)	X-ray diffraction analysis	10	samples

1-2 Preparation

1) Transportation of Materials and Equipment

After the customs clearance, the materials and the equipments were transported on the two 11 t trucks from the storage at the Callao port on August 18, 1983 to the Pampahuay village on August 20, through the villages of Churin and Oyon. On the way from the Pampahuay to the Iscaycruz camp, the transportation was done by three 1 t pickup trucks.

2) Excavation of Drill Chambers

In the underground, each one drill chamber along the Adit-N and along the Adit-S, that is, total 2 underground drill chambers, were prepared by excavating walls of the tunnels.

3) Water Supply for Drilling

For the drill holes of IC-6 and IC-7, approximate 600 meters of pipe-line was established and the necessary water was supplied by pumping, from the lake located north of the Cumbre de Limpe.

For the drill holes of IC-8 and IC-9, approximate 800 meters of pipe-line was established and the necessary water was supplied by natural flowing from the lake located south of the Cumbre de Limpe.

4) Preparation Period

Totalling 28 days were needed for the preparation works, that is transportation of materials and equipment, temporary construction of electric cable and pipe-line and others.

1–3 Drilling Operations

HQ wire-line method was employed for the drilling. Casing pipes were sunk on necessity so that the final diameter of the hole should be BQ-size.

1) IC-6

Hole length	:	200.30 m
Core length	:	165.10 m
Core recovery		82.4 %
Date commenced	:	September 20, 1983
Date completed	:	October 23, 1983

 $0 \text{ m} \sim 1.50 \text{ m}$:

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in the rocks belonging to the Chimu Formation down to the depth of 1.50 meters, where, as the wall was recognized to be stable, HW casing pipes were sunk to the depth of 1.50 m after reaming the hole by HQ wire-line bits.

1.50 m ~ 52.20 m :

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in quartzite to the depth of 52.20 meters.

In the portion at the depth between 35.00 m and 38.00 m, was recognized a clay fracture zone, where the insertion of rods was difficult and the hole was cemented. After reaming the hole by HQ wire-line bits, NW casing pipes were sunk to the depth of 49.00 meters.

52.20 m ~ 106.00 m :

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in shale, sandstone and in dolostone with clay to the depth of 106.00 meters.

In the portion between the depth of 56.10 m and 60.00 m, was recognized a clay fracture zone in dolostone, where the hole condition was worse because of the wall-swelling. After reaming the hole by HQ wire-line bits, NW casing pipes were sunk to the depth of 74.00 meters. $106.00 \text{ m} \sim 122.80 \text{ m}$:

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in dolostone with clay and in sulphide ore zone to the depth of 122.80 meters.

This part of the hole was recognized to compose a clay fracture zone in dolostone. The hole condition was extremely poor owing to the wall-swelling. At the depth of 122.80 meters, jamming happened.

It took one day to recover from the jamming. After the recovery, NW casing pipes were sunk to the depth of 122.80 meters.

122.80 m ~ 133.30 m :

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in clay fracture zone of sulphide ores to the depth of 133.30 meters. In the clay fracture zone of sulphide ore, the hole condition was poor owing to the wall-swelling. By reaming the hole with NW casing diamond shoe bit, NW casing pipes were sunk to the depth of 133.30 meters.

133.30 m ~ 157.60 m :

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in clay fracture zone of sulphide ores as well as in clay beds to the depth of 157.60 meters.

This part of the hole was recognized to compose a clay fracture zone of sulphide ores and

the hole condition was extremely poor owing to the wall-swelling. At the depth of 157.60 meters, jamming happened.

It took two days to recover from the jamming. After the recovery, NW casing pipes were sunk to the depth of 157.60 meters.

157.60 m ~ 200.30 m :

By BQ wire-line diamond bits, using bentonite mud water, the hole was excavated in dolostone beds, in sulphide zone to the depth of 200.30 meters, where the drilling was completed as the purpose of this hole was accomplished.

In the portion between 182.20 m and 186.25 m of the depth, zinc indications were caught and the mineralization was confirmed.

2) IC-7

Hole length	:	242.80 m
Core length	:	201.40 m
Core recovery	:	82.9 %
Date commenced	:	October 28, 1983
Date completed	:	December 15, 1983

 $0\,m\simeq 2.50\,m$:

By 116 mm diamond bit, using bentonite mud water, the hole was excavated in quartzite to the depth of 2.50 meters, where, as the wall was recognized to be stable, HW casing pipes were sunk to the depth of 2.50 meters.

 $2.50 \text{ m} \sim 7.40 \text{ m}$:

By HQ wire-line diamond bits, using bentonite mud water, the hole was excavated in quartzite to the depth of 7.40 meters, where, as the wall rocks were recognized to be stable, NW casing pipes were sunk to the depth of 7.40 meters.

 $7.40 \text{ m} \sim 138.80 \text{ m}$:

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in the Chimu Formation composed of dolostone bed, shale, sandstone as well as in clay fracture zone to the depth of 138.80 meters.

In the portion of the depth between 135.80 m and 137.80 m, was recognized a clay fracture zone in dolostone, where the hole condition was poor because of the wall-swelling, and it was difficult to drill any further. By reaming the hole with BW casing carbide shoe bit, BW casing pipes were sunk down to the depth of 138.80 meters.

138.80 m ~ 171.10 m :

By BQ wire-line diamond bits, using bentonite mud water, the hole was excavated in sul-

phide ore zone with clay as well as in limestone to the depth of 171.10 meters. In the portion of the depth between 151.00 m and 167.20 m, were recognized clay fracture zones of sulphide ores and druses, where the hole condition was poor as the water circulation was mostly lost. By reaming the hole with BW casing carbide shoe bit, BW casing pipes were sunk to the depth of 171.10 meters.

171.10 m ~ 242.80 m :

By BQ wire-line diamond bits, using bentonite mud water, the hole was excavated in limestone, dolostone, sulphide ores, shale and in clay fractured zone, by cementing the hole in parts to get over jamming state down to the depth of 242.80 meters, where the drilling was completed as the purpose of this hole was accomplished.

3) IC-8

Hole length	:	202.80 m
Core length	:	190.00 m
Core recovery	:	93.7 %
Date commenced	:	December 20, 1983
Date completed	:	January 13, 1984

 $0\,m \sim 0.50\,m$:

By HQ wire-line diamond bit, using bentonite mud water, the hole was excavated in quartzite to the depth of 0.50 meters, where, as the wall was recognized to be stable, HW casing pipes were sunk to the depth of 0.50 meters, by reaming the hole with HW casing diamond shoe bit. $0.50 \text{ m} \sim 2.00 \text{ m}$:

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in quartzite to the depth of 2.00 meters, where, as the wall was recognized to be stable, NW casing pipes were sunk to the depth of 2.00 meters, by reaming the hole with NW casing diamond shoe bit. $2.00 \text{ m} \sim 115.40 \text{ m}$:

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in the Chimu Formation composed of sandstone, dolostone and in fracture zones of sandy sulphide ores down to the depth of 115.40 meters.

In the portion of the depth between 99.10 m and 115.40 m, were recognized druses and fracture zone of sandy sulphide ores where water flew out (600 l/min, PH=2). Since the hole condition became poor there, the hole was reamed with BW casing diamond shoe bit and BW casing pipes were sunk to the depth of 115.40 meters.

115.40 m ~ 147.40 m :

By BQ wire-line diamond bits, the hole was excavated in fracture zones of sandy sulphide

ores to the depth of 147.40 meters. In a fracture zone of sandy sulphide ores, where water flew out (600 l/min, PH=2), jamming state happened. By reaming the hole with BW casing diamond shoe bit, BW casing pipes were sunk to the depth of 147.40 meters.

147.70 m ~ 202.80 m :

By BQ wire-line diamond bits, the hole was excavated in fracture zones of sandy sulphide ores as well as in specularite bed, in dolostone bed and in shale bed to the depth of 202.80, where the drilling was completed as the purpose of the hole was accomplished.

4) IC-9

Hole length	:	270.10 m
Core length	:	251.35 m
Core recovery	:	93.1 %
Date commenced	:	January 18, 1984
Date completed	:	January 31, 1984

0 m ~ 1.00 m :

By 116 mm diamond bit, using bentonite mud water, the hole was excavated in quartzite to the depth of 1.00 meter, where, as the wall was recongnized to be stable, 112 mm casing pipe was sunk.

 $1.00 \text{ m} \simeq 1.50 \text{ m}$:

By NQ wire-line diamond bit, using bentonite mud water, the hole was excavated in quartzite to the depth of 1.50 meters, where, as the wall was recognized to be stable, NW casing pipes were sunk to the depth of 1.50 meters, by reaming the hole with NW casing diamond shoe bit. $1.50 \text{ m} \sim 180.20 \text{ m}$:

By NQ wire-line diamond bits, using bentonite mud water, the hole was excavated in the Chimu Formation composed of sandstone, dolostone and shale with inserted clay layers, to the depth of 180.20 meters.

In a fracture zone of shale with clay insertions, where water flew out (50 l/min, PH=1), the hole condition was poor owing to the wall-swelling, and BW casing pipes were sunk to the depth of 180.20 meters.

 $180.20 \text{ m} \sim 270.10 \text{ m}$:

By BQ wire-line diamond bits, the hole was excavated in dolostone, in specularite layers and in sulphide ore zones to the depth of 270.10 meters, where the drilling was completed as the purpose of this hole was accomplished.

1-4 Mobilization and Removal

1) Mobilization

The number of days used for mobilization is given as follows.

IC-7 :	3 days
IC-8 :	3 days
IC9 ;	3 days

2) Removal

As the climate was unfavorable and the condition of the roads for transportation was poor while removal of the equipment from the drill site of IC-9 (Adit-S), it was necessary to repair were adjusted and stored at the camp after transportation of 13 km distance. Three days were used for removal.

1–5 Performance of the Drilling

1) Drilling Efficiency

As shown A. 1-8, with regard to drill holes totalling 916.00 meters, the drill length per shift was 2.39 m/shift, and that of real drill works was 3.93 m/shift.

The drilling pace and the number of bit rotation are given as follows.

	Drilling Pace	Number of Bit Rotation
Hard rocks	$1.0 \sim 1.5$ cm/min	450 ~ 600 г.р.т.
Moderate rocks	$1.5 \sim 2.0$ cm/min	350 ~ 450 r. p .m.
Soft rocks	2.0 ~ 2.5 cm/min	250 ~ 350 r.p.m.

2) Core Recovery

As shown in A. 1-8, 807.85 meters of cores were recovered against 916.00 meters of the total length of the drill holes.

The average core recovery was 88.2%.





Fig I-I PROGRESSIVE RECORD OF DIAMOND DRILLING IC-6



.





Fig. 1-3 PROGRESSIVE RECORD OF DIAMOND DRILLING IC-8



i.

CHAPTER 2 GEOLOGY AND MINERALIZATION IN THE DRILL HOLES

2-1 IC-6

(1) Purpose : The purpose of this hole was to explore mineralization along the lower extension of the hanging-wall-side orebody caught by the drill-hole DDH-4, as well as along the lower part of the Santa Formation, that is, along the boundary zone between the Santa Formation and the Chimu Formation.

(2) Location : At the point 310 m deep from the gate of the Adit-N, at the altitude of 4,692 meters above sea level. The bearing of the hole was 280°, and the inclination was -40° . The depth of the hole was 200.3 meters (Fig. 5, Fig. 6).

(3) Lithology : Down to the hole depth of 53.0 meters, the rocks were of the Chimu Formation which was composed mainly of quartzite with the inserted layers of shale, sandstone and dolostone.

To the hole depth of 94.2 meters, transitional zone of the Chimu Formation was recognized, comprising sandstone, dolostone, marl and shale.

Further down below the depth of 94.2 meters, the Santa Formation appeared. To the depth of 117.8 meters, alternation of dolomitic sandstone, dolostone and shale was found. Heavy dissemination of sphalerite, chalcopyrite and pyrite was recongnized in them. Down to the depth of 157.3 meters, massive pyrite was recognized associated with chalcocite and chalcopyrite. The matrix was clayey and the recovery was poor.

Below the depth of 157.3 meters, dolostone inserted with shale layers was recognized to the bottom of the hole, 200.3 meters. Dolomite was replaced by siderite in parts. Galena and sphalerite were disseminated in the siderite layers, where gypsum druses were also recognized. Sulphide layers composed of pyrrhotite and pyrite were developed in parts of the depth of $182.2 \sim 186.3$ m (Fig. I-5, Pl. I-6).

(4) Mineralization and grade : The analysis results of the ore samples collected from the indications of mineralization and from the mineralized parts are given as follows.

Depth (m)	Length (m)	Number of Samples	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)
96.8 - 101.0	4.2	4	4	0.03	0.85	5.24
108.0 - 115.0	7.0	5	15	0.32	0.02	21.59
115.0 - 122.8	7.8	4	23	2.48	0.02	0.46
122.8 - 145.0	22.2*	5	15	1.04	0.02	0.23

* Core recovery was poor.

(5) Discussion : The massive pyrite orebody caught by this drill hole (depth : $117.8 \sim 157.3$ m) was recognized to contain copper ores, as a whole. The principal copper minerals were chalcopyrite, associated with chalcocite and bornite. Pb-Bi minerals were recognized in chalcopyrite (A. III-2). This indication of copper mineralization is corresponding to the northern and lower extension of the massive pyrite orebody caught along the crosscut of the Adit-N. Along the peripheral zone of this massive pyrite orebody, that is, along the boundary with the Chimu Formation (depth 108.0 ~ 115.0 m), high grade zinc ores were recognized.

The bottom of this hole was still in the siderite zone of the Santa Formation. The siderite was leucocratic and of the species rich in Mn-component by X-ray diffraction (A. III-5).

2-2 IC-7

(1) Purpose : This hole was aimed to explore mineralization and to obtain geological information at the depth of the area where the Adit-N crosscut was located.

(2) Location : At the same point as the drill hole IC-6. The bearing of the hole was 250° , and the inclination was -60° . The depth of the hole was 242.8 meters (Fig. 5).

(3) Lithology : Down to the hole depth of 71.6 meters, the rocks were of the Chimu Formation which was composed mainly of quartzite, with the insertion of shale, sandstone and dolostone. Down to the depth of 122.0 meters, transitional zone of the Chimu Formation was recognized, comprising quartzite, sandstone, marl and shale. Below 1.4 meters of clay zone at the depth of 122.0 meters, the Santa Formation was recognized, which was composed of limestone, dolostone and marl inserted with thin layers of shale. The cores between 138.3 m and 167.2 m of the depth was mainly composed of pyrite, and the core recovery was poor. No cores were recovered between 154.9 m and 167.2 m of the depth, but it is estimated that this part would be represented by druses of pyrite or soft and weak clayey pyrite zone. Pyrrhotite and pyrite were recognized between 216.0 m and 223.0 m of the depth. Shale was predominant below the depth of 223.0 meters, and it is thought that the Carhuaz Formation appeared at the depth of 237.2 meters (Fig. I-6, PL. I-7).

(4) Mineralization and grade : No remarkable copper-lead-zinc mineralization was caught in and around pyrite orebody.

(5) Discussion : It was clarified by this drill hole that the size of the pyrite orebody would be smaller in the deep part below the crosscut of the Adit-N, and that the copper-lead-zinc mineralization would be less intense there.

2-3 IC-8

(1) Purpose : The purpose of this hole was to explore mineralization in the area south of the surface drill hole IC-5.

(2) Location : at the point 270 meters deep from the gate of the Adit-S. The altitude was 4,573 meters above sea level. The bearing of the hole was 250° and the inclination was -30° . The length of the hole was 202.8 meters. The area was corresponding to the portion below the small outcrop found in the area where talus deposits were accumulated (Fig. 5, Fig. 6).

(3) Lithology : To the depth of 70.5 meters, was recognized the Chimu Formation, which was composed mainly of quartzite, with the insertions of shale and sandstone. Transitional zone of the Chimu Formation was found to the depth of 95.0 meters, which was composed of sandstone, shale and marl.

The Santa Formation was recognized below the depth of 95.0 meters. The most of the Santa Formation found in the core of this drill hole was mineralized and altered to appear dark grey or greenish in color. Pyrite was recognized between 109.5 m and 148.3 m of the depth, but the matrix of this part was clayey and the cores were in powdered condition. Alternation of altered rocks and specularite-pyrite layers with chalcopyrite dissemination was found between 148.3 m and 184.7 m of the depth.

Below the depth of 184.7 meters, shale was predominant, and viewing from the fact that the sandstone insertions were recognized at around the depth of 200 meters, it was estimated that the rocks were belonging to the Carhuaz Formation.

(4) Mineralization and grade : Apparent thickness of the pyrite orebody caught in this hole was as much as 39 meters, but the orebody was found to be mono-mineral orebody of pyrite. In case specularite should appear instead of pyrite, chalcopyrite dissemination was recognized. The main copper-mineralization was as follows.

Depth (m)	Length (m)	Number of Samples	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)
150.5 - 154.0	3.5	3	tr	0.50	0.02	0.93
159.2 - 163.8	4.6	1	40	2.59	0.02	0.30
174.5 - 178.1	3.6	3	23	2.43	0.11	0.11

(5) Discussion : Remarkable mineralization and alteration were recognized as a whole of this drill hole. Silicification was intense in the quartzite of the Chimu Formation, which was extremely hard, associated with sericite.

In the shale of the Chimu Formation, pyrophyllite was identified by X-ray diffraction

(IC-8-026). In the specularite mass, talc was identified (IC-8-152). Under microscope, chalcopyrite in the specularite mass was associated with bornite and sphalerite, and around the specularite crystals, magnetite was found to be associated (IC-8-152).

2--4 IC-9

(1) Purpose : The purpose of this hole was to explore mineralization in the deep part below the drill hole IC-8.

(2) Location : At the same site as the hole IC-8. The bearing of the hole was 250° , and the inclination was -80° . The length of the hole was 270.1 meters (Fig. 5).

(3) Lithology : To the depth of 138.2 meters, was recognized the Chimun Formation, which was composed mainly of quartzite with inserted layers of dolostone, shale, marl and sandstone. To the depth of 184.7 meters, transitional zone of the Chimu Formation was recognized, comprising quartzite, sandstone, dolostone, marl and pelitic altered rocks.

Below 0.7 meters of clay zone at the depth of 184.7 meters, the Santa Formation was recognized. To the depth of 195.3 meters, altered rocks were found disseminated with hematite, and from the depth of 195.3 meters to the bottom, massive pyrite orebody was recognized. Siliceous and argillaceous portions with residual banded structure were contained in this massive pyrite orebody. These portions were estimated to have been originated from shale (Fig. I-7, PL. I-9). (4) Mineralization and grade : Intense mineralization and alteration were recognized in this hole as seen in the hole IC-8. The extension of the pyrite orebody was apparently more than 75 meters over most of the Santa Formation. However, the orebody was found to be monomineral orebody of pyrite.

(5) Discussion : Viewing the results of the geophysical exploration, the area where the holes of IC-8 and IC-9 were located was corresponding to the moderate anomaly of FE (Frequency Effect) value and to the high anomaly of AR (Apparent Resistivity) value, and some intense mineralization had been expected. However, by the results of the drilling of these two holes, it was large-scaled pyrite mono-mineral orebody that was caught. It is noted for future exploration that copper-lead-zinc concentration would be expected in the peripheral zone of pyrite orebody.




Fig. I-5 Geological Section for IC - 6




Fig. I-6 Geological Section for IC-7 and Crosscut




Fig. 1-7 Geological Section for IC-8 and IC-9

PARTICULARS PART I TUNNELLING EXPLORATION

PART II TUNNELLING EXPLORATION CONTENTS

Chapter	1	Tunnelling Exploration II-1
	1-1	Outline of the Exploration II-1
	1-2	Road Construction II-3
	1-3	Temporary Construction II-3
	1-4	Excavation II-3
	1–5	Adit-N Excavation II-4
	1–6	Adit-S Excavation II-5
Chapter	2	Geology and Mineralization in Tunnels II-6
	2-1	Adit-N II-6
	2–2	Adit-N, Crosscut II–6
	2–3	Adit-S 11–7

LIST OF APPENDICES

A. II-1 Summary of Program A. II-2 Details of Employed Days for Advance A. II-3 Summary of Performance A. II--4 List of the Used Equipment and Apparatus for Tunnelling A. II-5 Summary of Advance Works, Adit-N A. II-6 Summary of Advance Works, Adit-S A. II-7 Summary of Material Consumption A. II-8 Details of Material Consumption A. II-9 Surveying Results, Adit-N A. II-10 Surveying Result, Adit-N, Crosscut A. II–11 Surveying Result, Adit-S

А.	III-1	Assay Results
A.	III-2	Summary of Microscopic Observations
А.	III-3	Microscopic Observations of Polished Section
А.	III-4	Microphotograph
А.	III—5	Summary of X-Ray Diffraction Analysis
А.	III-6	X-Ray Diffraction Chart

.

CHAPTER 1 TUNNELLING EXPLORATION

1-1 Outline of the Exploration

Following the tunnelling exploration in the last year, 1982, the main tunnel was extended and the crosscut and the drilling chambers were excavated as to the Adit-N, while the main tunnel was extended and the drilling chamber was excavated as to the Adit-S, in the present year of 1983 (Fig. 5). It is noted that extra 20 meters of excavation was carried out for the crosscut of the Adit-N, considering the geological condition to the 130 m point.

The length and specifications of the tunnels and duration and other working conditions are as follows.

(1) Length of the tunnels

Name	Planned length (m)	Excavated length (m)
Adit-N	350.0	351.2
Adit-S	330.0	330.1
Total	680.0	680.3

(2) Specifications of the tunnels

Effective Section :	2.6 m x 2	.5 m
Inclination :	1/100 ~ 1	/200
Elevation of gate	Adit-N :	4,689.37 m
	Adit-S :	4,570.14 m

Direction of tunnels

Name	Length (m)	Direction
Adit-N (main tunnel)	200.4	160°
Adit-N, Crosscut	150.8	250°
Adit-S (main tunnel)	330.1	330°

(3) Term of exploration

Total days spent for excavation and its related work are 265 days from July 22, 1983 to March 12, 1984, as shown in the Table A. II-1.

Excavation began on July 27 for the Adit-N and on August 11 for the Adit-S, as the temporary works and the replacement of the machinery required the period until July 26, because it took quite a time to repair the bridge in Pampahuay which had been broken by the coal trucks and because it was unexpectedly difficult to cut open the new road and to widen narrow road, due to hard basement rocks around the ridge.

(4) Working System

The road construction and the temporary works were carried out for eight hours per one shift and one shift per day, and the tunnel excavation was carried out for eight hours per shift and three shifts per day.

(5) Number of Workers

Personnel worked for tunnel excavation including the road construction and the temporary works are as follows.

Japanese engineers	2 men per day
Peruvian engineers	6 men per day
Excavation labourers	45 men per day
(including waste carrier	
and truck builder)	
Surface labourers	5 men per day
(storekeeper, mechanics	
and compressor operator)	
Other labourers	10 men per day
(road construction and	
temporary works)	
Chauffeurs of Jeep and pick-up truck	3 men per day
Cook	4 men per day

(6) Topographical Survey

The results of survey in the tunnels are shown in Table A. II $-9 \cdot 10 \cdot 11$, and PL. II $-1 \cdot 2 \cdot 3$ are maps of the tunnels.

(7) Geological Survey in Tunnels

The tunnels were geologically surveyed on the scale of 1 to 200 with stress laid on clarifying lithology, geological structure, mineralization and dislocation by faults.

Contents and number of the assay and analysis works are shown as follows.

- 1) Chemical analysis of the mineralized portions (Ag, Cu, Pb, Zn) 40 samples
- 2) Microscopic observation of polished sections 10 pieces
- 3) X-ray diffraction analysis 5 samples

.

1-2 Road Construction

Following the construction in the last year, of the 16 km road section to Iscaycruz from the starting point of the construction about 1.4 km south of Pampahuay, 0.8 km was newly constructed, 2.4 km section was widened and whole of the section was repaired. The construction was carried out by one bulldozer (D7-17A) and manual labour.

1–3 Temporary Construction

An additional lodging house (50 m²), with a galvanized sheet iron roofing was built.

In the vicinity of the gate of the Adit-N, ore pier was constructed in addition to waste pier.

Three fans were set in each tunnel of the Adit-N and the Adit-S for ventilation (Hitachi propeller 500). Temporary buildings with galvanized iron roofing were built for generater station (13 m^2) , one each at every gate of the Adit-N and the Adit-S. For the doors (duplicated doors) of the underground magazine and the storage, two heavy locks were set for the outer doors and a lock for the inside doors. It is noted that an iron box (inside wooden) was fixed with anchor bolts to keep blasting cops inside in the storage. Lightning-conductor was prepared at the gate of the Adit-S and near the underground magazine.

Major machinery and major buildings constructed are listed in Table A. II-4.

1-4 Excavation

Personnel and working hours of excavation are as follows.

(1) Engineers

- Adit-N : Hideo Morishita Anibal Campos Ernesto Sosa Jorge Penasel
- Adit-S : Ken Nakamura Luis Manrique Alejandro Cartolin Emilio Guanhuayo

(2) Personnel

Excavation personnel for each adit is one Japanese engineer, three Peruvian engineers and 25 labourers, totaling 29 men. Excavation was carried out by one engineer and seven labourers per shift on three shifts per day.

(3) Working Hours

The first shift :	7:00 - 15:00
The second shift:	15:00 - 23:00
The third shift:	23:00 - 7:00

1-5 Adit-N Excavation

The figures shown are the distance from the gate. (excavated length in 1982 was 310.4 m) 1) Main Tunnel

310.4 m ~ 476.6 m :

Excavation was carried out following the last year's excavation. The rocks are quartzite. Remarkable joints and fractures of the NNW-SSE system are well developed and the excavation was difficult. At the 310.0 m point, a drilling chamber was prepared. Three fans were set and utilized for the deflation of smoke and gas after blasting, as well as for the air ventilation.

476.6 m ~ 496.6 m :

The rocks are still quartzite, but as there are many fractures of ENE-WSW system, total 5 timbers were required; 3 timbers in the section between 184.0 m and 186.2 m and 2 timbers in the section between 174.6 m and 176.0 m.

496.6 m ~ 510.8 m :

The rocks are quartzite, but fractures of ENE-WSW system are well developed and the excavation was difficult.

2) Crosscut

Opening \sim 33.0 m :

The rocks are those of the Chimu Formation composed mainly of quartzite. Remarkable joints are developed at around the 22.0 m point, and 5 timbers were required in the sections between 20.8 m and 23.2 m and between 31.7 m and 33.0 m.

 $33.0 \text{ m} \sim 71.0 \text{ m}$:

The rocks are those of the transitional zone of the Chimu Formation composed of alternation of sandstone, shale and dolostone, which are brittle in parts. Total 13 timbers were required in the section between 33.0 m and 38.9 m, between 40.4 m and 51.3 m and between 63.7 m and 65.5 m.

71.0 m ~ 80.0 m :

The rocks are those of the Santa Formation, which are easily broken, and 2 timbers were required in the section between 77.8 m and 79.3 m.

80.0 m ~ 115.0 m :

The rocks are different and remarkable mineralization was observed, though the mineralization was composed mainly of pyrite in this area. In this mineralization zone, 5 timbers were required in the section between 113.2 m and 117.7 m.

115.0 m ~ 137.2 m :

After passing through the mineralization zone, the rocks are composed of alternation of dolostone, limestone and shale. No timbering was necessary in this section.

137.2 m ~ 149.2 m :

Another mineralization zone is recognized, which is orebody containing sphalerite and pyrite.

149.2 m ~ 150.8 m :

The rocks are shale (supposed to belong to the Carhuaz Formation), in which numerous joints are developed densely.

1-6 Adit-S Excavation

270.1 m ~ 518.1 m :

Lithologically, hard quartzite of the Chimu Formation appeared continuously, as was the case in the last year. Average drilling rate was 15 cm per minute and 48 to 52 drill holes were required for one blasting. Therefore, excavation was very slow and consumption of drilling bit became very heavy. In the section between 317.7 m and 318.4 m, fracture zone with clay was recognized and 2 timbers were required.

Three fans were set and utilized for the deflation of smoke and gas after blasting as well as for the air ventilation.

518.1 m ~ 600.2 m :

In the far side of the 518.1 m point, remarkable faults are recognized and the rocks are represented by alternation of shale, mari and sandstone. As there are extremely weak portions, total 33 timbers were required: 3 timbers in the section between 520.6 m and 523.9 m, 13 timbers in the section between 526.9 m and 545.4 m, 5 timbers in the section between 551.1 m and 557.1 m, and 12 timbers in the section between 560.5 m and 576.7 m.

CHAPTER 2 GEOLOGY AND MINERALIZATION IN TUNNELS

2–1 Adit-N (main tunnel)

The excavated length of the Adit-N (main tunnel) in the first year was 310 meters and that in the present year was 200 meters. The cummulative total length is 510 meters. The direction of this Adit-N is 160° (PL. I-3 · 4).

By the observation of the geology in the tunnel, quartzite of the Chimu Formation is recognized over whole of the length from the 310 m point, the starting point to the 510 m point, the ending point in the present year. The quartzite is leucocratic or light grey in color, and is fine to medium grained, massive, compact and hard. The strike is $N15^{\circ} \sim 20^{\circ}$ W, and the dip is as steep as $80^{\circ} \sim 85^{\circ}$ to the east. The quartzite contains, in places, shale layers as thick as $5 \sim 10$ cm with the spacing of several ten centimeters, and joints of the NNW-SSE system are well developed in this direction, parallel to the bedding planes. Also, in the direction almost rectangular to the bedding planes, joints of WNW-ESE system are densely developed, and in places they seem to be fracture zone (around the 490 m point). At around the 350 m point, a fault fracture zone of NW-SE system has recognized, dipping $25^{\circ} \sim 35^{\circ}$ to the southwest.

2-2 Adit-N, Crosscut

The opening of the crosscut of the Adit-N is at the 310 m point from the gate of the main tunnel. The direction of the crosscut is 250° and its length is 150 m (PL. I $-3 \cdot 5$).

As to the geology along the crosscut of the Adit-N, the Chimu Formation is recognized to the 31 m point from the opening, composed mainly of quartzite with inserted layers of shale, dolostone and sandstone. The strike of the Chimu Formation is $N15^{\circ} \sim 25^{\circ}W$. and the dip is $75^{\circ} \sim 90^{\circ}E$. In the comparatively soft layers of shale and dolostone in contact with the hard quartzite, fractured zone or faults are developed in many cases. At the 15 m point and at the 23 m point, faults of NW-SE system with the dip of $35^{\circ} \sim 50^{\circ}SW$ are developed.

Within 39 meters of the width from the 31 m point to the 70 m point, alternation of dolostone, shale, sandstone and quartzite is recognized, which is correspondent to the transitional zone of the Chimu Formation. Faults of NW-SE system are developed with the dip of 80°SW at the 48 m point, and with the dip of 30°SW at the 52 m point. These faults of NW-SE system are accompanying fault clay as wide as 10 \sim 20 cm and fracture zone as wide as several ten centimeters, and it is estimated that these faults have dislocated the beds in fair amount. Viewing from the fault clay and from the structure of the fracture zone, they are thought to be reverse fault. In the dolostone close to the Santa Formation, dissemination of sphalerite is recognized, and the,

	Length (m)	Number of Samples	Ag (g/t)	Cu (%)	Pb (%)	Zn _(%)
Right wall (north side)	12	12	11	0.11	0.10	17.11
Left wall (south side)	12	12	5	0.08	0.04	17.16
Average	12	24	8	0.10	0.07	17.13

This orebody is, as seen from the assay results, composed of simple ores mostly of sphalerite and pyrite. In the far part of this orebody in the crosscut, remarkably fractured shale is recognized. It is possible that they are belonging to the Carhuaz Formation.

2–3 Adit-S (main tunnel)

The Adit-S (main tunnel) was excavated in the first year in the length of 270 m, and the excavation length in this year is 330 m. The cummulative total is 600 meters. The direction of the tunnel is 330° (PL. II-4-2 · 3 · 4).

Geologically, the Adit-S is situated in the Chimu Formation as a whole from the 270 m point, the start in this year, to the 600 m point, the ending point.

To the 500 m point, is recognized quartizite, which is heavily silicified, leucocratic, massive, compact and hard. Pyrite is disseminated in this quartzite extensively. Where thin layers of shale and sandstone (usually the thickness is less than 5 cm) are inserted in the quartizate, bedding plane joints are well developed in parallel with these thin layers of shale and sandstone. The quartzite has the strike of N20°W and the dip of $65^{\circ} \sim 70^{\circ}$ E, showing overturned structure. Joints of ENE-WSW system are well developed almost rectangular to the bedding planes. At the points of 319 m and 404 m, faults of the ENE-WSW system (trend N70°E, dip 80° ~ 90°N, containing clay zones of the approximate width of 50 cm) are recognized. At the 500 m point, a fault fracture zone of the width of 1.2 meters is recognized in the direction of N55°E, dipping $60^{\circ} \sim 80^{\circ}$ to the south. Bounded by this fault, sandstone bed as thick as 0.8 meters is found in the far side. Fault zone is recognized in 17 meters from the 520 m point to the 537 m point. This fault zone is composed of the faults of NNE-SSW system and the faults of ENE- WSW system. Beyond this fault zone, alternation of marl, sandstone, shale and quartzite is observed. The marl is light brown, massive and soft. The sandstone is leucocratic and has fissilities. The shale is dark grey and has schistosity. The tunnel was totally timbered from the 520 m point, where the fault is located, to the 577 m point, where the alternation zone is distributed.

average grade of 5 samples collected in 9 meters along the wall is Cu 0.37%, Pb 0.11%, Zn 2.29% and Ag tr. The minerals composing this dolostone are mainly Fe-rich ankerite and quartz by the result of the X-ray diffraction (CN-5-20, A. III-5).

The Santa Formation is recognized in far side of the 70 m point. To the 79 m point, alternation of marl and shale is found, heavily altered and mineralized with the dissemination of sphalerite and pyrite. Banded structure is observed in green and white bands in this alternation. It has been clarified by the X-ray diffraction that the green bands are composed of great amount of chlorite (CN-6-30, A. III-5).

Within 36 meters of the width from the 79 m point to the 115 m point, massive pyrite orebody is recognized. The matrix of the pyrite orebody is clayey in some cases and is siliceous in other cases. In case of clay matrix, the ore is extremely soft and easily powdered. In this orebody, there are many druses over 1 meter in diameter. The average grade of 9 samples collected in this orebody is Cu 1.48%, Pb 0.08%, Zn 0.27% and Ag tr. In the central part of the pyrite orebody, only slight mineralization is observed as to any of copper, lead and zinc. It has been clarified that zinc is concentrated along the peripheral zone of the orebody while copper centration is in the inner zone of the periphery. As a whole, the general trend of this orebody is roughly N20°W with the dip of 85°E, but at around the 90 m point, gently-inclined structure with the dip of 20°W is developed, which is thought to be some partial peculiar structure blocked by faults.

From the 115 m point to the 137 m point, alternation of limestone, shale and dolostone is recognized, not mineralized. The limestone around the orebody is dolomitized. The fact that the orebody is in contact with unmineralized rocks with quite sharp boundary is thought to suggest that the mineralization would have been heavily controled by the bedding plane faults and the fracture zones developed in parallel with the bedding planes.

Within 12 meters of the width between the 137 m point and the 149 m point, there is an orebody of zinc mineralization. The matrix of this orebody is pyrite, and sphalerite is recognized in patches, in irregular veinlets and in dissemination in pyrite mass. The zinc grade of the ore is roughly Zn 15% in most cases, but there are some portions where the grade is as high as more than Zn 20%. The assay results of the samples collected by continuous channel sampling with 1 meter interval along both walls are shown below.

APPENDICES PART I DATA OF DRILLING

12

A. .

;例

LIST OF APPENDICES

- A. I-1 List of the Used Equipment for Drilling A. I-2 Articles of Consumption and Drilling Parts Preparation and Removal Records A. I--3 A. I--4 Operation Results of Drill Hole, IC-6 Operation Results of Drill Hole, IC-7 A. I-5 A. I-6 Operation Results of Drill Hole, IC-8 A. I-7 Operation Results of Drill Hole, IC-9 Summarized Operational Data of Each Drill Hole A. I-8 A. I–9 Working Time of Each Drill Hole A. I–10 Drilling Meterage of Diamond Bits
- A. I-11 Specifications of Diamond Bits

-

A. I-I List of the Used Equipment for Drilling

Item	Mode1	Quantity	Capacity, Type, and Specification	Item	Model	Quantity	Capacity, Type, and Specification
Drilling Machine	TQ1-3C	1	Capacity NO 510m, BQ 660m	Drill Rods	HQ-VL	2	1-50 m/FC
			Inner Diameter of Spindle 93mm Weight (except engine) 2,300 kg	n	NQ-WL	100	3.00 m/PC
Pump	NAS-3C	1	Piston ϕ 75mm Capacity 130, 72 39, 22 ℓ/min Pressure 26 \sim 40 kg/cm ²	"	u	2	1.50 m/PC
	{			"	BQ-WL	100	3.00 m/PC
78	NAS-3B	1	Piston $\sqrt[4]{5}$ mm Capacity 130, 72, 39, 22 l/min Pressure 26 \sim 40 kg/cm ²		34	2	1.50 m/PC
11	MS-303	1	Piston #25mm Capacity 25 ~ 41 1/min	Casing Pipes	112	5	3.00 m/PC
			Pressure 35 kg/cm ²			4	1.00 m/PC
Engine for pump	2T-90L	1	Diesel Engine 1,800 rpm/20 PS			2	0.50 m/PC
19	NS-65C	1	Diesel Engine 1,800 rpm/S.5 PS	17	HW	10	3.00 m/PC
Electric Motor for Drilling Machine	NV180M4	1	Electric Motor 1,750 rpm/30 HP	н	u	4	1.00 m/PC
Electric Motor for Drilling pump	NV1 32N4	1	Electric Motor 1,745 rpm/12 HP	u	17	2	0.50 m/PC
Electric Motor for	NV100LA4	1	Electric Motor 1,730 rpm/3.6 HP		NW	70	3.00 m/PC
Electric Motor for Mud Mixer	NVIOULA4	ł	Electric Motor 1,730 rpm/3.6 HP	"	**	5	1.00 m/PC
Generator	SAR#76	۱	115 kW, 1,800 vpm/220V, 60 Hz	"	**	2	0.50 m/PC
Generator	TS-3.55	2	8.5 kW, 1,800 rpm/720V, 60 Hz		BW	90	3.00 m/FC
Generator	YSG-3.5	2	3.5 KVA, 220V, 60 Hz		,,	6	1.00 m/PC
Engine for Generator	NS-65C	2	Diesel Engine 1,800 rpm/5.5 PS	π		4	0.50 m/PC
Mud Mixer	MCE-200A	1	Volume 200 £, 800~1,000 rpm/min				
Submersible Pump	KTV-22L	1	2.2 kW, 3P, 220V, 60 Hz, 0.6 m ³ /min				
Transformer	50KVA	4	50 KVA, 3P, 3,300 V/210V				
Rod Holder	RH-85	1	Hand Type				
Drill Rods	HQ-WL	10	3.00 m/PC				

A. I-2 Articles of Consumption and Drilling Parts

				Qua	untity	
Item	Specification	Unit	IC-6	1C-7	IC-8	IC-9
Light oil		£	16,100	17,130	9,680	7,400
Gasoline		٤	214	295	140	130
Mobil oil		2	164	305	105	140
Hydraulic oil		2	40	10	-	10
Grease		kg	10	20	5	12
Bentonite Libonite	50kg/bag	kg	188	326	69	107
Libonite Tel-cellose		kg	142	255	60	136
		kg	39	80	11	31
Tel-stop Speeder-P		kg L	6	264	-	-
Cement	40kg/bag		65	45 82	49	-
Metal crown	40kg/bag 116mm	Bag Pc	12	82	49	18
Single core tube	114mm x 0.5m	rc Set	-			2
Hire line core barrel	HQ x 1.50m	sec	ī	_	-	1
Are line core parret	NO x 1.50m		•	1	-	1
	BQ x 1.50m		_	<u></u>	1	-
Inner tube assembly	HQ x 1.50m		-		-	1
m n	NO x 1.50m		_	_	1	<u>.</u>
PP 11	BQ x 1.50m	**	_	1		-
Outer tube	HQ x 1.50m	Pc	-	-	-	-
**	NO x 1.50m	Pc	-	_	-	1
	BO x 1.50m		-		-	-
Inner tube	HO x 1.50m	н	-	-	-	-
**	NO x 1.50m	a	-	-	1	-
**	BQ x 1.50m,		-	- 1	-	1
Casing metal shoe	114 0m	17	- 1	-	-	-
41	HW	79	1	-	-	
*1	NW		4	-	-	-
	BW		1	2	-	-
Guide pipe	нQ		-	-		1
	NQ	**	-	1	-	1
**	BQ	**	-	1	*	1
Guide coupling	HQ	17 17	-	1	-	1
	NQ		-	1	-	1
.,	BQ		-	1	-	1
Core lifter case	HQ		-	1	-	1
	NQ		3	4	2	3
	BQ		2	E – 1	-	4
Core lifter	HQ		2 6	- 8	- 4	1
	NQ		6	8	4	6 2
Water swivel packing	BQ	**	4	Ā	4	2
Water swivel spindle		11	2	4	4	2
Suction hose	50mm x 4.5m	17	-	ī		1
Piston rod		. 11	2	2		2
A RECOIL FOR			4	1		4

* ****	Constat store			Qu	antity		
Item	Specification	Unit	IC-6	IC-7	IC-8	IC-9	
Valve steel ball	38.1 ø	Pc	8	-	8	8	
Pump packing			8	-	-	8	
V-belt	TGM-3C	Set	1	-	_	i	
	NAS-3B	"		1	-	1	
n	NAS-3Cx2T-90L	"	1	-	-	-	
	YSC-3.5xNS-65C		2	-	1	-	
Core box	HQ	Pc		2	-	1 -	
	NQ	"	29	28	29	41	
38	BQ	"	7	15	14	13	
Wire	10#	kg	15	10	15	12	
	12#	ч [.]	10	8	9	10	
Nail		"	10	8	12	6	
Wire rope	6mm x 550m	Roll	-	1	-	1	
	12 mm x 40 m	"	-	1	-	-	
Manila rope	18mm x 30m		1	-	1	-	
Vinyl rope	8mm x 100m	"	-	1	-	0.5	
Rag		kg	10	5	10	8	

÷

Ite	em	No.]]	LC-6	I	.C-7	1	C-8	I	C-9				
		In	21th	Aug. '83	25th	Oct. '83	17th	Dec. '83	15th	Jan. <u>'84</u>				
Access road	In	19th	Sep. '83	27th	Oct. '83	19th	Dec. '83	17th	Jan. '84					
		Out	24th	Oct. '83	16th	Oct. '83	14th	Jan. '84	lst	Feb. '84				
			24th	Oct. '83	16th	Oct. '83	14th	Jan. '84	4th	Feb. <u>'84</u>				
			Days	Man- shifts	Days	Man- shifts	Days	Man- shifts	Days	Man- shifts	Days	Man- shifts	Days	Man- shifts
	Access road		-	-	-	-	-	-	-	_				
E l	Haulage		6	132	0.5	11	1	22	0.5	11				
arat	Installation		18	252	2	44	1	22	2	44				
Prep	Water pipe		3	66	_	-	0.5	11	-	-				
-	Test run, etc.		3	66	0.5	11	0.5	11	0.5	11				
	Total		30	516	3	66	3	66	3	66				
	Dismantlin	Dismantling		11	0.5	11	0.5	11	1	22				
	Pipe remov	al	0.5	11	0.5	11	0.5	11	0.5	11				
ova	Haulage			-	-	-	-	-	2	44				
Removal	Road rein- statement		-	-	_	-	-	-	-	_				
	Others		-	-	-	-	-	-	0.5	11				
	Total		1	22	1	22	1	22	4	88				
	Grand Total		31	538	4	88	4	88	7	154				

A. I-3 Preparation and Removal Records

A – 3

Working Period		Period			Number of Days	Actual Workin Days		Total Number of Workers	
	Preparation	n 21th Aug.'83∿19th Sep.'83			30	28	2	616	
	Drilling	20th Sep.'83~23th Oct.'83			34	33	1	682	
	Removing	24th Oct.'83∿24th Oct.'83			1	1	-	22	
	Total	21th Aug. '83~24th Oct		Oct.'83	65	62 3		1,320	
Drilling Length	Planned Length	m 200.00	Over- burden	-		covery	for each 100) m section	
	Increase or Decrease in Length	m	Core Length	m 165.10			Section	Total	
	•	m			0~100	m	93.7 %	93.7 %	
	Length Drilled	200.30	Core Recovery	82.4%	100~200	.30m	69.8 %	82.4 %	
Working Time	Drilling	195°00'	21.4%	19.6%		m	7	7	
	Hoisting & Lowering Rod	59°00'	6.5%	5.9%		m m	%	% %	
	Hoisting & Lowering I.T	78°00'	8.6%	7.9%		m	%	%	
	Miscellaneou	11aneous 566°00'		62.2% 57.1%		Efficiency of Drilling			
	Repairing	12°00'	1.3%	1.2%	200.30m/Working		g Period	3.08m/day	
	Others	-	- %	- %	200.30m/Working D		g Days	3.23m/day	
	Total	910°00'	100 %	91.7%	200.30m/Drilling		ng Period	5.89m/day	
	. Preparation	1 40°00'	-	4.1%	200.30m/Net Drilling Days		6.07m/day		
	Moving	42°00'	-	4.2%					
	G. Total	992°00'		100 %	Total workers/200.30m 6.59 Man/r		6.59 Man/m		
ng Pipe Inserted	Pipe Size & Meterage	Inserted Length Drilling Length	% Recove		Total Drilling Workers/200.30m 3.40 Ma			3.40 Man/m	
	HW 1.50 m	0.7 7	. 100	100 %		Hoisting&Lowering Rod 47 Times I.T. 239 Times			
	NW 133.30 m	66.6 %	6 7	79 %					
	BW 157.60 m	78.7 %	3 80) %	Remarks				
Casing					G : Grand				
о 					I.T.: I:	nner Tul	be		

A. I-4 Operation Results of Drill Hole, IC-6

-

•

Period]	Period		Number of Days	Actual Workin Days		Day Off	Total Number of Workers
	Preparation	25th Oct.	'83v27th (Oct.'83	3	3			66
Working	Drilling	28th Oct.	'83∿15th	Dec.'83	49	39		10	840
ork	Removing	16th Dec.	'83∿16th I	Dec.'83	1	1		-	22
12	Total	25th Oct.	'83∿16th	Dec.'83	53	43		10	928
Length	Planned Length	m 240.00	Over- burden	m	Core Re	covery	for	each 100	m section
Drilling Le	Increase or Decrease in Length	m	Core Length	m 201.40	Dept of Hole		S	Section	Total
l i l	*	m			0~100	m		96.7 %	96.7 %
	Length Drilled	242.80	Core Recovery	82.9%	100~200	m		67.4 %	81.1 %
	Drilling	202°00'	22.7%	21.5%	200~242	.80 m		93.5 %	82.9 %
	Hoisting & Lowering Rod	42°00'	4.7%	4.5%		 m		7. 7.	7.
e	Hoisting & Lowring I.T.	72°00'	8.1%	7.7%		m		%	7
Time	Miscellaneou	is 551°00'	61.9%	58.7%		Effici	ency	of Dril	ling
Working	Repairing	23°00'	2.6%	2.5%	242.80	m/Worki	ng F	Period	4.58 m/day
lork Iork	Others	-	- %	- %	242.80	m/Worki	ng D	ays	5.65 m/day
	Total	890°00'	100 %	94.9%	242.80	m/Drill	ing	Period	4.96 m/day
	Preparatio	n 36°00'	ł	3.8%	242.80	m/Net D	rill	ing Days	6.22 m/day
	Moving	12°00'		1.3%	Total w	orkers/	242.	80 m	3.82 Man/m
	G. Total	938°00'		100 %					
rted	Pipe Size & Meterage	Inserted Length Drilling	, Recov	very of ng Pipe				ļ	3.46 Man/m
Insert	mererage	Length		nê rehe		g&Lower 2 Ti	ing mes		g&Lowering 44 Times
	HW 2.50 m	1.0 5	7 1(00 %	·				,
Pipe	NW 7.40 m	3.0 5	7 10	00 %	Remarks	•			
l g	BW 171.00 m	70.4 5	7	88 %		rand	_		
Casing	······································				1.T.: I	nner Tu	be		
Ľ									

A. I-5 Operation Results of Drill Hole, IC-7

Period			Period	. <u> </u>	Number of Days	Actual Working Days	5	Day Off	Total Number of Workers
	Preparation	17th Dec.	83~19th 1	Dec.'83	3	3		_	66
Working	Drilling	20th Dec.	'83~13th	Jan.'84	25	20		5	440
lor	Removing	14th Jan.	84~14th .	Jan.'84	1	1			22
	Total	17th Dec.	'83~14th .	Jan.'84	29	24		5	528
Length	Planned Length	m 200.00	Over- burden	m	Core Re	covery f	or	each 100	m section
Drilling Le	Increase or Decrease in Length	m	Core Length	m 190.00	Dept of Hole		5	Section	Total
l II		m		ĺ	0∿100) m		96.0 %	96.0 %
	Length Drilled	202.80	Core Recovery	93.7%	100~202	.80 m 91.3 %		93.7 %	
	Drilling	180°00'	44.8%	36.6%		m		%	7
	Hoisting & Lowering Rod	46°00'	11.4%	9.3%		m m		%%	%
Time	Hoisting & Lowering I.T	. 72°00'	17.9%	14.6%		m		7	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
	Miscellaneou	s 80°00'	19.9%	16.3%		Efficie	ncy	of Dril	ling
Working	Repairing	_	- %	- %	202.80m	Working	; Pe	riod	6.99m/day
Mo	Others	24°00'	6.0%	4.9%	2 02. 80m	/Working	De	iys	8.45m/day
	Total	402°00'	100 %	81.7%	202.80m	n/Drillin	ıg F	Period	8.11m/day
] [🖁 Preparatio	n 36°00'	+	7.3%	202.80m	Net Dri	11i	ng Days	10.14m/day
	Moving	54°00'	-	11.0%	Total w	orkers/2	02.	80m	2.60 Man/m
	G. Total	492°00'	-	100 %		·			
rted	Pipe Size &	Inserted Length	Recov	very of	Total Drillin	g Worker	s / 2	02.80m	2.16 Man/m
Insert	Meterage	Length	s casti	ıg Pipe		g&Loweri 6 Tim		Hoistin I.T.	g&Lowering 182 Times
Pipe	HW 0.50 m	0.3 7		0 %	Remarks	<u>_</u>		1	
Pi	NW 2.00 m	1.0 %)0 %		rand			
ing	BW 147.40 m	72.7 %		57 %		nner Tub	۵		
Casing				<u></u>		uner 140	-		
<u>ц </u>		<u> </u>	I		L				

A. I-6 Operation Results of Drill Hole, IC-8

-

ſ	eriod]	Period		Number of Days	Actua Worki Days		Day (Dff	Total Number o Workers	
Ì	Per	Preparation	15th Jan.	'84~17th	Jan.'84	3	3		-		66	7
ļ	LING	Drilling	18th Jan.	'84~31th	Jan.'84	14	14		-		308	٦
٠	Working	Removing	lst Feb.	'84 ~4th	Feb. '84	4	4		-		88	
	Mc	Total	15th Jan.	'84 ~4th	Feb.'84	21	21		-		462	
	Length	Planned Length	m 250.00	Over- burden	m	Core Re	ecovery	for	each	100) m section	n
	Drilling L	Increase or Decrease in Length	m	Core Length	m 251.35	Dept of Hold		S	ectio	on	Total	
	Dri		m			0~100) m	1	00	%	100	%
	-	Length Drilled	270.10	Core Recovery	, 93.1%	100∿200) m		96.5	%	97.9	%
F		Drilling	177°00'	54.6%	45.4%	200∿27(0.10 m		79.2	%	93.1	73
	ĺ	Hoisting & Lowering Rod	26°00'	8.0%	6.7%		m m	- <u></u>		% %		78 78
	Time	Hoisting & Lowering I.T	. 32°00'	9.9%	8.2%		m			%		%
		Miscellaneou	s 53°00'	16.4%	13.6%		Effi	cienc	y of	Dri	lling	
1	kin(Repairing	36°00'	11.1%	9.2%	270.10m	n/Worki	ng Pe	riod		12.86m/day	у
	Working	Others	-	- %	- %	270.10r	n/Worki	ng Da	ys		12.86m/day	у
		Total	324°00'	100 %	83.1%	270.10m	n/Drill	ing P	eriod	1	19.29m/day	у
		🖉 Preparatio	n 24°00'	-	6.1%	270.10n	n/Net D	rilli	ng Da	ays	19.29m/day	у
	ļ	Moving	42°00'	-	10.8%	Total v	vorkers	/270.	10 m		1.71 Man,	/m
		G. Total	390°00'		100 %	(D - 4 - 1	<u></u>		<u></u>			
	Inserted	Pipe Size & Meterage	Inserted Length Drilling Length		overy of Ing Pipe		ng&Lowe			stir	1.14 Man, ng&Lowering 258 Times	g
		114mm 1.00m	0.37 5	ζ]	100 %							
	Pipe	NW 1.50m	0.55 %		00 %	Remarks G : (-					
	Casing	BW 184.50m	68.30 5	<u>تا</u>	.00 %		Grand Inner T	ире				
	Ű						·····.,					

A. I-7 Operation Results of Drill Hole, IC-9

Drill hole	Type of		Drilling	(Core	No. of di	rilling	shift	Drillin	g speed	
No.	machine	Drilling period	length	Length	Recovery	Drilling	Casing etc.	Total	* m/shift	** m/shift	Remarks
IC - 6	TGM-3C	20th Sep. '83	200.30 ^m	m 165.10	82.4	67	56	123	2.99	1.63	
IC - 7	TGM-3C	28th Oct. '83 ∿ 15th Dec. '83	242.80	201.40	82.9	74	74	148	3.28	1.64	
IC - 8	TGM-3C	20th Dec. '83 ∿ 13th Jan. '84	202.80	190.00	93.7	50	14	64	4.06	3.17	
IC - 9	TGM-3C	18th Jan. '84 ∿ 31th Jan. '84	270.10	251.35	93.1	42	7	49	6.43	5.51	
					 			·			
	T	otal	916.00	807.85	88.2	233	151	384	3.93	2.39	

A. I-8 Summarized Operational Data of Each Drill Hole

* Drilled per one shift covering net drilling operations.

** Drilled per one shift covering total works conducted.

A - 8

.

Drill hole		Hoisting	& lowering & I.T.	Mi	scellaneo	ous				
No.	Drilling	Rod	Inner tube	Casing insertion	Hole reaming	Others	Repairs	Others	Movin g Operation	Total
IC - 6	195°00'	59°00'	78°00'	72°00'	156°00'	338°00'	12°00'	-	82°00'	992°00'
IC - 7	202°00'	42°00'	72°00'	18°00'	210°00'	323°00'	23°00'	-	48°00'	938°00'
IC - 8	180°00'	46°00'	72°00'	42°00'	30°00'	8°00'	-	24°00'	90°00'	492°00'
IC - 9	177°00'	26°00'	32°00'	18°00'	18°00'	17°00'	36°00'	-	66°00'	390°00'
1										
Total	754°00'	173°00'	254°00'	150°00'	414°00' 1,250°00'	686°00'	71°00'	24°00'	286°00'	2,812°00'

A .	I -9	Working	Time	of	Each	Drill	Hole
------------	------	---------	------	----	------	-------	------

A – 9

•

Item	Size	*		Drilling	, meterage	by drill	hole. Un	ite meter						Drilling	g meterage	by drill	hol. Unit	e meter	
item		Туре	BIT No.	IC-6	10-7	10-8	10-9		Total	Item	Size	Type	Bir No.	10-6	IC-7	1C-8	10-9		Total
			E-1293	-	2.00	•	•		2,00			NQ-HL	1034	2	m	14.50	n 1		14.50
	116mm	116mm	E-1294				0.30		0.30				1034			2.40	ł		2.40
			E-1295				0.50		0.50				1036			2.40	12.60		12.60
			Total	-	2.00		0.80		2.80				1037				18.10		18.10
		HQ-WL	P-1022	(0.50)					(0.50)				1038			ľ	11.80		11.80
			P-1023	(1.00)					(1.00)		SX	1	1039				19.20		19.20
	нх		P-1024	(2000)	1.10				1.10		ůA.		1039				17.60		17.60
ľ			P-1025		1.30				1.30				1040				16.70		16.70
			P-1026			0.50			0.50				1041				17.20		17.20
			Total	(1.50)	2.40	0.50	-		2.90				1041				20,50		20.50
		NQ-WL	4513	20.60					20.60				1044				18.50		18.50
			4514	19.80					19.80				1045				17.10		17.10
			4515	9.60					9.60				1046				10.10		10.10
			4516	22.10					22.10	Bit			Total	157.60	133.90	119.00	179.40		589.90
			11007	19.80					19.80			BQ-WL	P-1029	21.50					21.50
			11008	21.50					21.50				P-1030	21.20			1		21.20
Bit			11009	23.90					23.90				P-1031		11.50				11.30
			11010	20.30					20.30				P-1032		9.10				9.10
			11011		19.40				19.40				P-1033		12.20				12.20
			11012		21.10				21.10				P-1034		15.10				15.10
			11013		22.10				22.10				P~1035		16.20				16.20
	NX		11014		17.80				17.80				P-1036		8.90				8.90
			11015		23.60				23.60				P-1037		10.20	ł	[[10.20
			11016		21.10				21.10		вх		A-47486		15.60				15.60
1			11017		8.80				8.80				47148Z		5.70				5.70
			11018			12.60			12.60				471485			20.50	1 1	}	20.50
ļ			11019			10.20			10.20				471486			21.10			21.10
- 1			11020			9.70			9.70				0-1407			19.60	E [19.60
			15312		1	4.80			4.80			1	D-7063			22.10	{		22.10
			15313			15.70			15.70				E-7078		1	ł	22.70		22.70
			1030			9.20			9.20				E-7079				21.80		21.80
ļ			1031			20.10			20.10				E-7080		l	ļ	18.90		18.90
	:]	1032			8.60			8.60				E-7081				26.50		26.50
			1033			11.20			11,20				Total	42.70	104.50	83.30	89.90		320,40
																			i i

A. I-IO Drilling Meterage of Diamond Bits

A - 10

.

ŧ

Size	Туре	Carats per bit	Matrix	Stones per carat	Water way	Number	Remark
		42	x	1/30	6	E-1293	Reset
116aaa	116mm	42	X	1/30	6	E-1294	
		42	X	1/30	6	E-1295	
	HQ-WL	40	Z	1/30	6	P-1022	Reset
		40	Z	1/30	6	P-1023	17
нх		40	x	1/30	6	P-1024	18
ļ		40	x	1/30	6	P-1025	77
		40	х	1/30	6	P-1026	*
	NQ-WL	30	x	1/30	4	4513	Reset
		30	x	1/30	4	4514	- 11
		30	x	1/30	4	4515	
		30	х	1/30	4	4516	4
		30	T ₁	1/30	4	11007	4
[30	T ₁	1/30	4	11008	
		30	T ₁	1/30	4	11009	"
		30	T ₁	1/30	4	11010	*1
		30	т ₁	1/30	4	11011	*1
		30	τ ₁	1/30	4	11012	79
		30	тı	1/30	4	11013	*•
NX		30	T ₁	1/30	4	11014	**
		30	τ ₁	1/30	4	11015	4
		30	T,	1/30	4	11016	4
		30	T ₁	1/30	4	11017	5
		30	T ₁	1/30	4	11018	••
		30	T ₁	1/30	4	11019	4
		30	T ₁	1/30	4	11020	ts
		30	x	1/30	4	15312	
		30	х	1/30	4	15313	••
		30	x	1/30	4	1030	••
		30	x	1/30	4	1031	4
		30	х	1/30	4	1032	11
		30	х	1/30	4	1033	

Size	Type	Carats per bit	Matrix	Stones per carat	Water way	Number	Remark
	NQ-WL	30	Y	1/30	4	1034	Reset
		30	Y	1/30	4	1035	"
		30	Y	1/30	4	1036	u.
		30	Y	1/30	4	1037	19
		30	Y	1/30	4	1038	
NX		30	Y	1/30	4	1039	
		30	z	1/30	4	1040	н
		30	z	1/30	4	1041	"
		30	z	1/30	4	1042	17
		30	z	1/30	4	1043	**
		30	z	1/30	4	1044	
		30	z	1/30	4	1045	11
		30	z	1/30	4	1046	"
	BQ-WL	20	z	1/30	4	P-1029	Reset
		20	z	1/30	4	P-1030	**
		20	z	1/30	4	P-1031	u
		20	z	1/30	4	P-1032	u u
		20	z	1/30	4	P-1033	
		20	z	1/30	4	P-1034	••
		20	z	1/30	4	P-1035	
		20	z	1/30	4	P-1036	
		20	T ₁	1/30	4	P-1037	
вх		20	τ ₁	1/30	4	A-47486	"
		20	т	1/30	4	471482	
		20	T ₁	1/30	4	471485	*
1		20	τ ₁	1/30	4	471486	14
		20	T ₁	1/30	4	D-1407	
		20	T ₁	1/30	4	D-7063	71
		20	Y	1/30	4	E-7078	
		20	Y	1/30	4	E-7079	
		20	Y	1/30	4	E-7080	"
		20	Y	1/30	4	E-7081	u

A. I-11 Specifications of Diamond Bits

A - 11



LIST OF APPENDICES

А.	II-1	Summary of Program
Α.	II–2	Details of Employed Days for Advance
А.	II3	Summary of Performance
А.	II-4	List of the Used Equipment and Apparatus for Tunnelling
А.	II-5	Summary of Advance Works, Adit-N
А.	II–6	Summary of Advance Works, Adit-S
А.	II–7	Summary of Material Consumption
Α.	II-8	Details of Materials Consumption
А.	II—9	Surveying Result, Adit-N
А.	II-10	Surveying Result, Adit-N, Crosscut

- A. II–10
- A. II-11 Surveying Result, Adit-S

A. II-1 Summary of Program

	Item	1983 Jun.	Jul.	Aug.	Sept.	Oct.	Nov.	Dec.	1984 Jan.	Feb.	Mar.	Apr.
1	Mobilization (Tokyo ~ Lima ~ Site)	10 15		15 19								
2	Road Construction Restoration Construction Repair		11 24 10	17	18						8	
3	Equipment Moving in Provisional Works (with housing)		8 23									
4	Advance Adit-N 351.2 m Adit-S 330.1 m		27 [¹¹					5	18		
5	Equipment Moving out								10 11 []	25 28		
6	Demobilization (Site ~ Lima ~ Tokyo)										9 16	
7	Preparation of Report										17	10

4

•

A. I-2 Details of Employed Days for Advance

	Moving in	_		Period of	Advanci	ng Work			Detail Workin	s of g Period	Р	rincipa	11 Accessory	Works	
Adit Name	Moving out	Camping	No.of Days	Advance	No.of Days	Boring Chamber	No.of Days	Total	Work- ing Days	Suspend- ed Days	Construc- tion Re- pair of Road	No.of Days	Moving in Provision	No.of Days	Total No.of Days
	Accessory	(Date)	day	(Date)	đay	(Date)	day	day	day	days	(Date)	day	(Date)	day	day
	Works														
	(Date)				1						10,Ju1,83		8,Ju1,83		
	10,Jul,83							Ì			8,Mar,84	180	23,Ju1,83	8	188
	8,Mar.84														
Adit-N		25, Jul, 83		27,Jul,83		15,Aug,83									
		27,Ju1,83	3	5,Jan.84	135	28,Aug,83	13	151	151						<u> </u>
Adit-S				11,Aug,83		31,Aug,83									
				18,Feb,84	140	29,Sept,83	19	159	140	19					
	Moving out						:	<u> </u>							
	10,Jan,84														
	28,Feb.84													6	6
Total No. of Days			3		275	· · · · ·	32	310	291	19		180		14	194

Note ; No. of days of each term signifies the No. of days in working term.

A - 13

A. II-3 Summary of Performance

Adit	Moving in Moving out	No. of Working S		No. Man-	of shift	No. of Hours for Each Work								
Name		No. of Shift of Advance	Total No. of Shift	Engineer	Worker	Advance	Support	Besides Advance	Sub- Total	Camping Break up	Equipment Moving out	Others	Total	
(Accessory		(shift)	(shift)	(man-shift)	(man-shift)	(hrs.)	(hrs.)	(hrs.)	(hrs.)	(hrs.)	(hrs.)	(hrs.)	(hrs.)	
Works)	Road Restor.	0	9	9	86	-	-	-	-	-	-	86	86	
	" Constr.	4	22	13	169	32	-		32	-	-	176	208	
	" Repair	O	149	29.5	974	-	-	-	-	-	-	1,192	1,192	
	Provision		25	21.5	163	94	-	-	94	96	-	-	190	
Adit-N		435	468	552	3,813	2,731	112	325	3,168	24	-	-	3,192	
Adit-S		463	512	667.5	4,350	2,863	200	341	3,404	-	-	-	3,404	
	Equipment Moving out		23	28	68	-	-	-	-	-	36	60	96	
Total		902	1,208	1,320.5	9,623	5,720	312	666	6,698	120	36	1,514	8,368	

Note : Provisional works contain equipment moving in and camping etc.

A – 14

.

.

Α.	∏-4	List of	the Used	Equipment	and	Appratus	for	Tunnelling	
	1 1 -			Edabuleur	ana	rippi acas		. annenne	

Name of Equipment	Type and Specification	No., Q'ty	Remarks
Compressor	ATLAS COPCO XA 350 1/S	2	1 for N, 1 for S.
Loader	ATLAS COPCO LM 36	1	for N.
	ATLAS COPCO LM 56	1	for S.
Drifter	ATLAS COPCO BBC-16W	6	3 for N, 3 for S.
Tub	Side Dump Type, Hand Handling		
	1.0m ³		
Bit Grinder	ATLAS COPCO LSD-61	1	
Generator	YAMMER YSG-35N	1	
	CATERPILLAR SR-4 325 KVA	1	1 for S.
	CATERPILLAR SR-4 69 KVA	1	l for N.
Ventilator	HITATHI 500¢ 3.7 KW	6	3 for N, 3 for S.
Bulldozer	CATERPILLAR D7-17A	1	
Vehicle	TOYOTA LAND CRUISER FJ-55	1	
	TOYOTA HIGH LOOKS	1	
	TOYOTA LAND CRUISER FJ-40		
House	Storied House, Galvanized Iron 13 m ²	2	Generator. 1 for N, 1 for S
	Storied House, Galvanized Iron 50 m ²	1	Camp House.
	Storied House, Galvanized Iron 94 m ²	1	Camp House.
	Storied House, Galvanized Iron 80 m ²	1	Kitchen, Dinning Room.
	Storied House, Galvanized Iron 190 m ²	1	Camp House. Office.
	Storied House, Galvanized Iron 18 m ²	1	Warehouse
	Storied House, Galvanized Iron 18 m ²	2	Compressor Chamber
			1 for N, 1 for S.
	Storied House, Galvanized Iron 18 m ²	2	Fuel Storage 1 for N, 1 for S.
Powder Magazine	Subterranean Type Powder Magazine	1	
	Subterranean Type Blasting Supplies		

						-					
5	Date	of Starting Work		22	, Jun, 198	3					
Construction Period	Date	of Starting Advan	ce	27	27, Jul, 1983						
Per	Date	of Terminating Ad	vance	5	5, Jan, 1984						
10	Date	of Finishing Work		11	, Jan, 198	4					
	\square			Until 5, Jan, 1984 Until 11, Jan, 1984							
Days			No.of Days Per cent		it (7)	t (Z) No.of Days		it (%)	Remarks		
of Necessary D	ing a	Advance	days 148	84.1	84.1	days 148	83.1	83.1			
	Working Days	Housing	-	-	-		-	-			
	3	Others	28 "	15.9	15.9		16.9	16.9			
	Sub-	Total	176 "	100.0	100.0	178 ^{II}	100.0	100.0			
No	Susp	ended Days	-	-	-	-	-	-			
	Tota	1	176 "	-	100.0	178 "	-	100.0			
			Perforation		Preparation of Advance, Housing		Accessory Other Works		Remarks		
Workers	Staff	Interior		men 504			-	men	1 man=8 hrs/Shift		
A M	ŝ	Surface		-	6		42	? 11			
Necessary	b Interior		3,598 "		-		-				
	Worker	Surface			29	el .	186				
of	Sub- Total	Interior	4,102 "		-						
No.	Suf Tot	Surface		_	35 "		228 "				
		Total	4,102 " 35		35	"	" 228 "		G. Total 4,365 men		
		<u> </u>	Until	5, Jan,	1984	Unti	1 11, Jan,	1984			
				(351.2 m)			(351.2 m))	Remarks		
сy	Adva 1 wo	nce m per rking day		1.995 m			1.973 m				
ficiency		nce m per tual Working day		2.373 m			2.373 m				
Efi		nce m per cessary day		1.995 m			1.973 m				
		nce m per cessary worker		0.086 m			0.080 m				
ort	No. d	of Support		30 se	ts						
Support	Timbering Length (Z)			30.1 m (8.6 %)						

A. II-5 Summary of Advance Works, Adit-N

-

.

-

g	Date	of Starting Work		22	, Jun, 198	3	_			
Construction Period	Date	of Starting Advance	.e	11,	Aug, 198	3		<u> </u>		
Peri	Date	of Terminating Adv	ance	18, Feb, 1984						
Col	Date	of Finishing Work		28, Feb, 1984						
			Until 18, Feb, 1984			Ünt	il 28, Feb			
Days				Per cen	nt (%)	No.of Days	Per cen	t (Z)	Remarks	
ary D	gu	Advance	days 159	84.6	76.8	days 159	82.8	75.4	(*) Leg Drills,	
of Necessary	Working Days	Housing		-	-	-		-	robbed 15-27,Aug,1983	
	3	Others	29_"	15.4	14.0	33 "	17.2	15.6	Compressor trouble	
No. 0	Sub-	Total	188 "	100.0	90.8	192 "	100.0	91.0	19-24,Sept,1983	
	Susp	ended Days (*)	19 "	-	9.2	19 "		9.0	Loader trouble 18,0ct,1983	
	Tota	1	207 "	-	100.0	211 "	-	100.0		
				Perforation		Preparation of Advance, Housing		y Other	Remarks	
Necessary Workers	H Interior		шеп 644.5		nen -		men -		1 man=8 hrs/Shift	
ry W	S .	Surface			10		8	3 "		
essa	Worker	La Interior		3,985 "			-			
	Wor	Surface	-		30 "		335 "] .	
. of	Sub- Total	Interior	4,629.5 "		-		-			
No.	n Su	Surface		-	40 "		418 "			
		Total	4,62	9.5 "	40 "		418 "		G. Total 5,087.5 ^{men}	
			Until 18, Feb, 1984 (330.1 m)		Unti	1 28, Feb, (330.1 m)		Remarks		
cy		nce m per rking day		1.756 m			1.719 m			
fficiency		nce m per tual working day		2.076 m			2.076 m		<u></u>	
Ef		nce m per cessary day		1.595 m			1.564 m			
		Advance m per 1 necessary worker		0.071 m			0.065 m			
Suppori	No.	of Support		35 se	ts					
Ins	Timb	ering Length (Z)	44.	7 m (13.5	Z)					

A. II-6 Summary of Advance Works, Adit-S

Name	Specification	Q'ty		Remarks
Petroleum		123,776	l	
Gasoline		8,359	٤	
Drifter Oil		450.3	l	
Engine Oil		1,619	l	
Compressor Oil		3,916	l	
Grease		80.8	kg	
Dynamite	DINASOL 7/8"x7"	15,054.6	kg	
Detonator	FULMESA No.6	29,049	nos	
Fuse	FULMESA	172,251.9	ft	
Insert Bit	COROMANT 22m/m Hex.	893	nos	
	Gauge 38m/m 1.8m			
Carbide		212.5	kg	
Timbering Wood		15.5	m3	No includes Materials
Board		13.1	m ³	∫for Housing.
S1eeper		838	nos	
Supports		65 s	sets	

A. I-7 Summary of Material Consumption

Note: Includes road construction etc.

- - -

.

-

		Q'	ty	
Name	Specification	Adit-N	Adit-S	Remarks
Petroleum		60,570 L	63,206	
Gasoline		3,452 l	4,907	
Drifter Oil		200 L	250.3	
Engine Oil		792 l	827	
Compressor 011		1,953 l	1,963	Į
Grease		38 kg	42.8 kg	
Dynamite	7/8" x 7"	7,268.9 kg	7,785.7 kg	
Detonator	FULMESA No.6	14,253 nos	14,796 nos	
Fuse	FULMESA	85,743.1 ft	86,508,8 ft	
Insert Bit	COROMANT 22m/m Hex.	403 nos	490 nos	
	Gauge 38m/m 1.8m			
Carbide		119.5 kg	93 kg	
Timbering Wood	¢0.05 x 3.0m)			
	¢0.10 x 3.0m			
	Ø0.15 x 3.0m	- 3		}
	Ø0.20 x 3.0m	11 m ³	4.5 m ³	
	¢0.25 x 3.0m			ļ
	ø0.30 x 3.0m			
Board	0.3mx0.05mx1.8m	6.3 m ³	6.8 m ³	
Sleeper	0.15mx0.15mx1.2m	397 nos	441 nos	
Supports		30 sets	35 sets	

A. I-8 Details of Material Consumption

Survey	Direction	Horizontal Distance	Coordi	nate (m)	Elevation
Point	51100110	(m)	Longitude	Latitude	(m)
NI	-		310,344.28	8,809,084.30	4,689.37
N1 -N2	111°40'30"	20.329	310,376.21	8,809,077.06	4,689.73
N2 -N3	112°31'41"	33.641	310,407.28	8,809,064.17	4,690.29
N3 -N4	112°38'18"	22.963	310,428.47	8,809,055.33	4,690.49
N4 -N5	112°29'21"	22.632	310,449.38	8,809,046.68	4,690.54
N5 -N6	128°31'16"	10.849	310,457.87	8,809,039.92	4,690.62
NG -N7	158°21'26"	4.961	310,459.70	8,809,035.31	4,690.74
N7 -N8	173°29'56"	6.526	310,460.44	8,809,028.82	4,690.84
N8 -N9	159°56'06"	23.839	310,468.62	8,809,006.43	4,691.00
N9 -N10	159°59'31"	21.000	310,475.80	8,808,986.70	4,691.28
N10-N11	159°57'01"	26.255	310,484.803	8,808,962.037	4,691.578
N11-N12	159°54'11"	37.265	310,497.607	8,808,927.041	4,691.724
N12-N13	159°48'36"	23.576	310,505.743	8,808,904.914	4,691.719
N13-N14	159°44'56"	31.690	310,516.712	8,808,875.183	4,692.080
N14-N15	159°44'56"	24.488	310,525.188	8,808,852.209	4,692.231
N15-N16	159°49'46"	29.836	310,535.475	8,808,824.203	4,692.391
N16-N17	159°46'31"	22.620	310,543.294	8,808,802.978	4,692.491
N17-N18	159°46'31"	25.642	310,552.158	8,808,778.917	4,692.606
N18-N19	159°42'06"	30,309	310,562.672	8,808,750.491	4,692.797
N19-N20	159°32'06"	38.273	310,576.053	8,808,714.634	4,693.097
N20-N21	159°21'56"	28.736	310,586.179	8,808,687.742	4,693.305
N21-F		25.400			

A. I-9 Surveying Result, Adit-N

•

-

· •

A. II-10 Surveying Result, Adit-N, Crssscut osscut

Survey	Direction	Horizontal Distance	Coordia	Elevation	
Point	Difection	(m) Longitude		Latitude	(m)
N15			310,525.188	8,808,852.209	4,692.231
N15-CN4	248°02'06"	23.816	310,503.101	8,808,843.301	4,692.306
CN4-CN5	248°03'16"	24.249	310,480.610	8,808,834.239	4,692.564
CN5-CN6	247°57'51"	35.339	310,447.853	8,808,820.981	4,693.020
CN6-CN7	247°44'41"	31.479	310,418.720	8,808,809.059	4,693.413
CN7-CN8	247°43'01"	31.427	310,389.640	8,808,797.143	4,693.902
CN8-F		6.300			

Survey	Direction	Horizontal Distance	Coordin	nate (m)	Elevation
Point	DITCELION	(m)	Longitude	Latitude	(m)
S1	-	-	310,968.25	8,807,260.34	4,570.14
S1 -S2	359°30'37"	20.421	310,968.08	8,807,881.36	4,570.20
S2 -S3	1°04'22"	31.541	310,968.67	8,807,912.90	4,570.44
S3 S4	1°01'47"	24.693	310,969.11	8,807,937.59	4,570.76
S4 -S5	0°46'37"	19.689	310,969.377	8,807,957.273	4,570.91
S5 -S6	359°10'47"	33.582	310,968.90	8,807,990.85	4,571.21
S6 -S7	357°24'32"	8.190	310,968.53	8,807,999.03	4,571.33
s7 -s8	327°31'22"	26.245	310,954.44	8,808,021.17	4,571.572
S8 -S9	327°10'12"	21.519	310,942.769	8,808,039.254	4,571.852
S9 -S10	329°56'32"	29.518	310,927.985	8,808,064.802	4,572.241
s10-s11	330°53'42"	29.832	310,913.475	8,808,090.867	4,572.398
S11-S12	330°04'52"	23.450	310,901.779	8,808,111.191	4,572.496
S12-S13	330°01'02"	26.445	310,888.564	8,808,134.097	4,572.707
s13-s14	329°52'42''	35.288	310,870.856	8,808,164.619	4,573.225
S14-S15	329°54'02"	35.968	310,852.818	8,808,195.736	4,573.562
S15-S16	329°24'02"	38.090	310,833.429	8,808,228.521	4,573,587
S16-S17	329°15'37"	30.654	310,817.761	8,808,254.868	4,573.722
S17-S18	329°00'27"	38.379	310,797.999	8,808,287.767	4,574.209
S18-S19	329°38'32"	35.381	310,780.118	8,808,318.296	4,574.279
S19-S20	330°08'32"	31.319	310,764.526	8,808,345.457	4,574.437
S20-S21	329° 54 ' 57''	45.220	310,741.859	8,808,384.585	4,574.534
S21-F		15.100		L	

A. I-II Surveying Result, Adit-S

*

>

APPENDICES PART II GEOLOGICAL DATA

LIST OF APPENDICES

٠

- A. III-1 Assay Results
- A. III-2 Summary of Microscopic Observations
- A. III-3 Microscopic Observations of Polished Section
- A. III-4 Microphotograph

-

- A. III-5 Summary of X-Ray Diffraction Analysis
- A. III-6 X-Ray Diffraction Chart

Α.	Ⅲ -Ⅰ	1
----	-------------	---

Assay Results (1) Drilling Core

						-		(1)
No.	Sample No.	Depth (m)	Length (m)	Rock Type	Cu (%)	РЪ (%)	Zn (%)	Ag (g/t)
001	IC-6-095	94.2- 95.5	1.3	Ald	0.09	0.02	0.80	nd
002	IC-6-096	95.5- 96.8	1.3	Ald	0.02	0.16	1.90	
003	IC-6-097	96.8- 98	1.2	Ore	0.02	2.80	2.10	4
004	IC-6-098	98 - 99	1	Ore	0.02	0.12	4,85	4
005	IC-6-099	99 -100	ī	Ore	0.01	0.05	2.41	4
006	IC-6-100	100 -101	1	Ore	0.08	0.02	12.34	4
007	IC-6-101	101 -102	1	Ore	0.02	0.02	2.11	4
008	IC-6-103	102.0-103.5	1.5	Ald	0.02	0.27	1.41	4
009	IC-6-104	103.5-105.0	1.5	Ald	0.03	0.02	1.30	tr
010	IC-6-105	105.0-106.5	1.5	Ald	0.20	0.02	3.61	tr
011	IC-6-107	106.5-108.0	1.5	Ald	0.02	0.02	0.25	4
012	IC-6-108	108.0-109.3	1.3	Ald	0.03	0.02	6.42	4
013	IC-6-110	109.3-110.5	1.2	Ald	0.03	0.03	30.21	20
014	IC-6-111	110.5-112.0	1.5	Ald	0.28	0.02	22.88	4
015	IC-6-113	112.0-103.5	1.5	A1d	0.62	0.02	29.10	4
016	IC-6-114	103.5-115.0	1.5	Ald	0.56	0.01	19.06	44
017	IC-6-116	115.0-116.4	1.4	Ald	3.43	0.02	1.20	112
018	IC-6-117	116.4-117.8	1.4	Ald	4.59	0.01	0.30	4
019	IC-6-119	117.8-120.3	2.5	Ру	0.83	0.02	0.30	4
020	IC-6-121	120.3-122.8	2.5	Py	2.43	0.02	0.30	4
021	IC-6-124	122.8-126.4	3.6	Py	0.48	0.02	0.20	16
022	IC-6-127	126.4-130.4	4.0	Py	2.99	0.01	0.08	8
023	IC-6-131	130.4-135.9	5.5	Ру	0.58	0.02	0.08	16
024	IC-6-136	135.9-140	4.1	Ру	0.28	0.02	0.02	12
025	IC-6-140	140 -145	5	Ру	1.00	0.03	0.70	20
026	IC-6-145	145 -150	5	Ру	0.18	0.09	0.08	12
027	IC-6-150	150 -155	5	Ру	0.74	0.02	0.03	36
028	IC-6-155	155 -160	5	Ру	0.24	0.01	0.90	tr
029	IC-6-167	167.0-168.1	1.1	Sid	0.05	0.01	1.30	12
030	IC-6-181	180.9-182.2	1.3	Sid	0.04	0.02	3.51	4
031	IC-6-183	182.2-183.8	1.6	Ру	0.04	0.02	0.20	20
032	IC-6-184	183.8-185.4	1.6	Ру	0.03	0.03	0.30	tr
033	IC-6-186	185.4-186.3	0.9	Ру	0.01	0.75	3.91	tr
034	IC-6-193	192.8-194.4	1.6	Sid	0.02	0.03	1.65	tr
035	IC-6-195	194.4-195.9	1.5	Sid	0.01	0.01	1.60	12
036	IC-6-197	195.9-198.7	4.8	Sh	0.01	0.01	0.30	4
037	IC-6-199	198.7-200.3	1.6	Sid	0.02	0.02	0.60	4
038	IC-7-138	138 -140	2	Ру	0.13	0.06	0.36	4
039	IC-7-140	140 -142	2	Ру	0.06	0.03	0.75	nd
040	IC-7-142	142 -144	2	Ру	0.08	0.04	0.75	nd
041	IC-7-144	144 -146	2	Ру	0.11	0.02	0.03	nd
042	IC-7-146	146 -148	2	Ру	0.07	0.02	0.15	tr
043	IC-7-148	148 -150	2	Ру	0.05	0.03	0.13	tr
044	IC-7-150	150 -152	2	Py	0.04	0.02	0.06	tr
045	IC-7-152	152 -154	2	Ру Do	0.06	0.02	0.18	tr
046	IC-7-168	167.2-170.0	2.8	Do	0.05	0.04	0.90	tr
047	IC-7-179	178.4-179.5	1.1	Do	0.10	0.03	2.80	nd
048	IC-7-198	197.5-198.5	1.0	Do	0.01	0.02	0.30	nd
049 - 050	IC-7-207	206.5 - 207.8	1.3	Sid	0.02	0.02	0.90	tr
-050	IC-7-215	214.7-216.0	1.3	Do	0.05	0.02	0.60	tr

(1)

								(2)
No.	Sample No.	Depth (m)	Length (m)	Rock Type	Cu (%)	РЪ (%)	Zn (%)	Ag (g/t)
051	IC-7-216	216 -217	1	Py.Po	0.04	0.03	0.36	tr
052	IC-7-217	217 -218	1	Py.Po	0.03	0.02	0.08	4
053	IC-7-218	218 -219	1	Py.Po	0.05	0.02	0.25	tr
054	10-7-219	219 -220	1	Py Po	0.03	0.03	0.20	tr
055	IC-7-220	220 -221	ī	Py.Po	0.03	0.05	0.12	tr
056	1C-7-221	221 -222	1	Py.Po	0.04	0.03	0.20	tr
057	IC-7-222	222 -223	1	Py.Po	0.05	0.02	0.20	tr
058	IC-8-110	109.5-113.8	4.3	Py	0.05	0.04	0.08	nđ
059	IC-8-115	113.8-118.2	4.3	Py	0.04	0.02	0.15	nd
060	IC-8-119	118.2-122.7	4.5	Py	0.06	0.02	0.07	nd
061	IC-8-123	122.7-127.2	4.5	Py	0.06	0.01	0.08	nd
062	IC-8-128	127.2-131.6	4.4	Py	0.04	0.02	0.06	tr
063	IC-8-132	131.6-135.5	3.9	Py	0.04	0.02	0.07	tr
064	IC-8-136	135.5-138.8	3.3	Py	0.06	0.02	0.09	tr
065	IC-8-139	138.8-141.9	3.1	Py	0.06	0.02	0.06	tr
066	IC-8-142	141.9-145.1	3.2	Py	0.05	0.01	0.03	nd
067	IC-8-148	145.1-148.3	3.2	Py	0.04	0.01	0.10	nd
068	IC-8-149	148.3-150.5	2.2	Ald	0.06	0.01	0.90	tr
069	1C-8-151	150.5-151.6	1.1	Cu	0.24	0.02	0.70	tr
070	IC-8-152	151.6-152.8	1.2	Cu	0.87	0.01	1.51	tr
071	IC-8-153	152.8-154.0	1.2	Cu	0.36	0.02	0.55	nd
072	IC-8-154	154.0-156.8	2.8	Ald	0.12	0.02	2.46	nd
073	IC-8-157	156.8-159.2	2.4	Ald	0.07	0.02	2.31	tr
074	IC-8-160	159.2-163.8	4.6	Ald	2.59	0.02	0.30	40
075	IC-8-164	163.8-166.8	3.0	Ру	0.12	0.01	0.25	tr
076	IC-8-167	166.8-169.7	2.9	Ру	0.09	0.02	0.13	nd
077	IC-8-170	169.7-173.2	3.5	Ald	0.32	0.01	0.55	tr
078	IC-8-174	173.2-174.5	1.3	Spc	0.07	1.76	0.08	4
079	IC-8-175	174.5-175.8	1.3	Spc	0.74	0.23	0.20	32
080	IC-8-176	175.8-177.0	1.2	Cu	0.10	0.02	0.03	tr
081	IC-8-177	177.0-178.1	1.1	Cu	6.96	0.05	0.10	36
082	IC-8-179	178.1-180.3	2.2	Ald	0.03	0.02	0.15	tr
083	IC-8-181	180.3-182.5	2.2	Ald	0.02	0,02	0.03	tr
084	IC-8-183	182.5-184.2	1.7	Ald	0.01	0.02	0.85	nd
085	IC-9-185	184.7-190.0	5.3	Ald	0.08	0.03	0.04	tr
086	IC-9-190	190.0-195.3	5.3	Ald	0.10	0.02	0.03	4
087	IC-9-195	195.3-200	4.7	Py	0.02	0.02	0.01	tr
088	1C-9-200	200 -205	5	Ру	0.02	0.02	0.01	nd
089	IC-9-205	205 -210	5	Ру	0.05	0.01	0.08	4
090	IC-9-210	210 -215	5	Py D	0.06	0.02	0.09	3
091	IC-9-215	215 -220	5	Py D	0.06	0.01	0.01	nđ
092	10-9-220	220 -225	5	Py B	0.03	0.01	0.01	4
093	IC-9-225 IC-9-230	225 -230	5 5	Py Br	0.04 0.03	0.02 0.02	0.01 0.01	tr 132
094 095	IC-9-235 IC-9-235	230 -235 235 -240	5	Py Bu	0.03	0.02	0.01	3
095	IC-9-235	240 -245	5	Py Py	0.04	0.01	tr	tr
090	IC-9-240 IC-9-245	245 -250	5	ry Py	0.04	0.02	tr	tr
098	10-9-250	245 -255 250 -255	5	ry Py	0.05	0.02	nd	2
099	IC-9-255	255 -260	5	Py	0.03	0.02	nd	4
100	IC-9-260	260 -270	10	Py	0.03	0.02	nd	tr
100	10 / 200		~ ~	- ,				~-

(2)

٠

A - 24

.

-

А. Щ-	l Assag	y Re
-------	---------	------

esults (2) Tunnelling Sample

.

No.	Sample No.	Depth (m)	Length (m)	Rock Type	Cu (%)	Pb (%)	Zn (%)	Ag (g/t)
T01	CN-5-14	60 - 61	1	Ald	1.40	0.20	4.52	nd
T02	CN-5-16	62 - 63	1	Ald	0.12	0.07	1.61	nd
т03	CN-5-18	64 - 65	1	Ald	0.06	0.20	1.10	nd
т04	CN-5-20	66 - 67	1	Ald	0.24	0.07	1.72	nd
T05	CN-5-22	68 - 69	1	Ald	0.02	0.02	2.51	nd
T06	CN-5-29	75 - 76	1	Ald	0.12	0.05	0.60	4
T07	CN-5-33	79 - 80	1	Ру	1.49	0.02	1.20	tr
T08	CN-6-02	83 - 84	1	Ру	1.95	0.10	0.15	4
T09	CN-6-06	87 - 88	1	Py	0.07	0.05	0.15	tr
T10	CN-6-10	91 - 92	1	Ру	0.06	0,05	0.20	nd
T11	CN-6-14	95 - 96	1	Ру	0.06	0.05	0.08	nd
T12	CN-6-18	99 - 100	1	Ру	0.08	0.07	0.12	nd
T13	CN-6-22	103 - 104	1	Ру	0.18	0.10	0.10	tr
T14	CN-6-26	107 - 108	1	Ру	9.10	0.07	0.15	tr
T15	CN-6-30	111 - 112	1	Ру	0.32	0.20	0.30	tr
T16	CN-6-34	115 - 116	1	Ру	0.06	0.01	1.15	nd
T17	CN-7-24N	137 - 138	1	Ore	0.24	0.05	19.57	nd
T18	CN-7-25N	138 - 139	1	Ore	0.04	0.03	5.72	8
T19	CN-7-26N	139 - 140	1	Ore	0.03	0.65	14.75	60
T20	CN-7-27N	140 - 141	1	Ore	0.08	0.20	5.52	4
T21	CN-7-28N	141 - 142	1	Ore	0.10	0.05	14.55	8
T22	CN-7-29N	142 - 143	1	Ore	0.08	0.03	8.03	4
T23	CN-7-30N	143 - 144	1	Ore	0.09	0.04	22.18	4
T24	CN-7-31N	144 - 145	1	Ore	0.14	0.03	28.60	tr
T25 T26	CN-7-32N	145 - 146	1	Ore	0.10	0.05	24.49	16
T20 T27	CN-7-33N	146 - 147	1	Ore	0.12	0.03	17.06	8
T28	CN-7-34N	147 - 148	1 1	Ore	0.19	0.04	27.09	12
T29	CN-7-35N	148 - 149 137 - 138	1	Ore	0.07	0.02	17.76	8
T30	CN-7-24S CN-7-25S	137 - 138 138 - 139	1	Ore	0.09	0.07	12.85	4
T31	CN-7-26S	138 - 139 139 - 140	1	Ore Ore	0.03	0.07	13.75	4
T32	CN-7-275	139 - 140 140 - 141	1	Ore	0.04	0.02	4.82	16
T33	CN-7-28S	140 - 141 141 - 142	1	Ore	0.03	0.02 0.03	7.11 15.66	tr
T34	CN-7-295	141 - 142 142 - 143	1	Ore Ore	0.04 0.09	0.03		tr 12
T35	CN-7-305	142 - 143 143 - 144	1	Ore	0.09	0.02	16.45 23.68	4
T36	CN-7-315	145 - 144 144 - 145	1	Ore	0.14	0.03	26.70	4
T37	CN-7-325	144 - 145 145 - 146	1	Ore	0.12	0.02	20.70	4 tr
T38	CN-7-33S	145 - 140 146 - 147	1	Ore	0.12	0.03	27.00	8
T39	CN-7-34S	140 - 147 147 - 148	1	Ore	0.10	0.04	20.03	6 4
T40	CN-7-35S	147 - 143 148 - 149	1	Ore	0.08	0.05	16.96	4
- 70		170 17/	-	OLC	0.12	0.05	10.30	4

Abbreviations

Ore	:	Pb.Zn ore	Ald	;	Altered rock
Cu	:	Cu ore	Sid	:	Siderite
Py	:	Pyrite	Do	:	Dolomite
		Pyrrhotite	Sh	:	Shale
Spc	:	Specularite			

A. II-2 Summary of Microscopic Observations

Sample No.	Minerals Type	Sphalerite	Sphalerite 💥	Galena	Chalcopyrite	Pb-Bi mineral	Bornite	Covelline	Pyrite	Pyrrhotite	Arsenopyrite	Marcasite	Hematite	Magnetite	Pb-As mineral	Ti mineral	Graphite	Remarks ,
IC-6-098 IC-6-100 IC-6-112	Do-Ss Do-Ss Sp dis Sh Sp-Gl dis Sh Cp-v	•. 0	000	000000000000000000000000000000000000000	• • • •	•	•		• • • • • •		•		•					dis dis Gl is fgd in Sp Gl is fgd in Sp Bi and Bn are in Sp
IC-6-168 IC-6-181 IC-6-182 IC-7-106 IC-7-143	Sid Sp-Gl dis Sid Sp-Po-Py-ore Do Py-ore		•	• 0 0	•				00000	0						•	•	dis Sp in Po Py aggregation
IC-7-217 IC-8-116 IC-8-152 IC-8-160	Sid Po-Py-ore Py-ore Hm-ore Hm-ore	• • •	•		•		•		• 0 0	0			00	0	•			Py is auhedral Bn is with Cp
IC-8-167 IC-8-170 IC-8-177	Py-ore Py-ore Py-ore Cp-Hm-ore Py-ore	•			••••0		•	•	° 000		•		• 0 •	0				Cp is fgd in Py Cp is in Py and around Py Bn is with Cp,Cp is vs in Py

(1)

A 1 26

.

v: vein

dis: disseminated

Sphalerite with chalcopyrite dots o fairly

⊚ abundant

O common

. rare

Sample No.	Minerals Type	Sphalerite	Sphalerite 🕱	Galena	Chalcopyrite	Pb-Bi mineral	Bornite	Covelline		Pyrite	Pyrrhotite	Arsenopyrite	Marcasite	Hematite	Magnetite	Pb-As mineral	mineral	Graphite	Remarks
		Sp	Sp	Ga	сh	Pb	Bo	ŝ		Py	Py:	Ar	Ma	Hei	Ma	Pb	Ti	Gra	
CN-5-20	Do	0	ļ	1					1		•		•					o	
CN-6-24	Py-dis ore	•		•	•					O				•					Gl and Cp are fgd in Py
CN-7-17	Py-ore	•	ſ		•		•		ľ	\odot	•						[dis in Py
CN-7-24	Sp-Hm-ore	0	0	•	•									0			1		Gl is fgd in Sp
CN-7-26	Sp-Py-ore	0	0	•	•					0									dots of Cp in Sp
CN-7-28	Sp-drs	0	0	•	•					•			_						Gl is fgd in Sp
CN-7-29	Sp-Py-ore		0		•					\odot									
CN-7-31	Sp-Py-ore	0	•		•					0	•								Gl is fgd in Sp
CN-7-33	Sp-Py-ore	0	•	•	•					õ									· ·
CN-7-35	Sp-Py-ore	lõ.	•	•						õ									

v: vein

A – 27

dis: disseminated

*: Sphalerite with chalcopyrite dots

© abundant

t O common

• fairly • rare

Α.	ш-з	Microscopic	Observations	of Polished	Section

	А. Ш-З	Microscopic Observations of Polished Section (1)
Sample No.	Rock Type	Microscopic Observations
IC-6-091	Dolomite	Ore minerals recognized in this section are slight amount of pyrite and very slight amount of sphalerite and chalcopyrite. Pyrite is anhedral and is found disseminated. Sphalerite does rarely contain dots of chalcopy- rite and is scatteringly disseminated. Only a grain of chalcopyrite was recognized in this section. It is noted that unidentified minerals which could be taken as graphite are recognized.
IC-6-098	Dolomitic sandstone (Zn diss.)	Ore minerals recognized in this section are slight amount of pyrite, sphalerite and galena. Fyrite is euhedral-anhedral and is found to be scatteringly disseminated. Sphalerite rarely contains dots of chalcopy- rite and is recognized to be scatteringly disseminated. Galena is also recognized to be scatteringly disseminated.
IC-6-101	Dolomitic sandstone (Zn diss.)	Ore minerals recognized in this section are large amount of pyrite and sphalerite with small amount of galena and chalcopyrite. Pyrite is eu- hedral - anhedral and is recognized in form of dissemination or in por- phyritic texture. Sphalerite contains dots of chalcopyrite and is recog- nized to be disseminated or to occur around pyrite grains. Chalcopyrite is recognized to occur in dots contained in sphalerite. Galena is found to be fine grained, contained in sphalerite.
IC-6-112	Zn-Py ore	Ore minerals recognized in this section are large amount of sphalerite with small amount of pyrite, chalcopyrite and galena. Sphalerite contains dots of chalcopyrite and is found to occur in network. Chalcopyrite is recognized to occur in dots contained in sphalerite. Pyrite is euhedial - anhedral and is recognized to be scattered in sphalerite or in gangues. Galena is fine grained (several 10 µm), and is recognized to occur con- tained in sphalerite grains.
IC-6-129	Cu ore in vein	Ore minerals recognized in this section are very large amount of chalcopy- rite and large amount of sphalerite with small amount of pyrite, although slight amounts of hematice, galera, azurite, Pb-Bi series (?) minerals and arsenopyrite are recognized. Chalcopyrite is found to be massive and in some cases it is recognized to occur surrounding sphalerite. Sphalerite contains dots of chalcopyrite and is found to be contained in chalcopy- rite. Pyrite is euhedral and is found to be contained in chalcopyrite in many cases. Hematite is also found to be contained in chalcopyrite. Galena, azurite and Pb-Bi series (?) minerals are found to be fine grained (under 100 µm) and are recognized to be contained in sphalerite and chalco- pyrite (see photograph).
IC-6-168	Siderite	Ore minerals recognized in this section are small amount of pyrite and slight amount of Ti minerals (?) with very slight amount of galena. Pyrite is euhedral - anhedral and is found to be scatteringly disseminated. Ti minerals (?) are also found to be fine grained (several 10 µm) and is recognized to be scatteringly disseminated. Only one grain of galena has been found in this section in an approximate diameter of 100 µm. It is noted that the Ti minerals (?) could possibly be identified as sphalerite.
IC-6-181	Siderite (Zn diss.)	Ore minerals recognized in this section are small amount of sphalerite, galena and pyrite with slight amount of chalcopyrite. Sphalerite contains dots of chalcopyrite in parts, and is recognized to be disseminated and to occur in porphyritic texture or along veinlets. The occurrence of galena is similar to that of sphalerite. Pyrite is euhedral - anhedral and is found to be scatteringly disseminated.
IC-6-182	Zn-Po-Py ore	Ore minerals recognized in this section are very large amount of pyrrhotite and large amount of pyrice with small amount of sphalerite and galena. Pyrrhotite is found to be massive and includes pyrite, sphalerite and galena in some cases, while it is recognized to be surrounding them in other cases. Sphalerite rarely contains dots. Pyrite is euhedral in most cases. It is noted that pyrrhotite has been marcasitized along cracks or along the peripheral parts in contact with pyrite. It is thought that the order of the crystallization would have been pyrite + sphalerite and galena + pyrrhotite + marcasitization (see photograph).
IC-7-106	Dolomite	Ore minerals recognized in this section are small amount of pyrite and slight amount of sphalerite. Pyrite is euhedral - anhedral and is recog- nized to be scatteringly disseminated. Sphalerite rarely contains dots of chalcopyrite, and is found to be scatteringly disseminated. It is noted that there are some other minerals which seem to be graphite.
IC-7-143	Py massive ore	Ore minerals recognized in this section are very large amount of pyrite. Pyrite is euhedral - anhedral and is recognized to be aggregated or massive.

A - 28

•

(2)


Sample No.	Rock Type	Hicroscopic Observations
IC-7-207	Siderite	Ore minerals recognized in this section are small amount of pyrite. Fyrite is euhedral - anhedral and is found to be disseminated or aggregated.
IC-7-217	Po-Py ore	Ore minerals recognized in this section are very large amount of pyrite and pyrrohtite with slight amount of sphalerite. Pyrite is euhedral, and pyrrohtite is found to occur filling spaces among pyrite grains. Sphale- rite rarely contains dots of chalcopyrite, and is found around pyrite. Pyrhotite is found to occur surrounding sphalerite. Therefore, it is thought that the order of the crystallization would have been pyrite \rightarrow sphalerite \rightarrow pyrhotite.
IC-8-116	Py siliceous ore	Ore minerals recognized in this section are very large amount of pyrite and slight amount of sphalerite. Pyrite is euhedral - anhedral, and massive. Sphalerite rarely includes dots of chalcopyrite. It is fine grained (under 200 µm) and is recognized to occur in and around pyrite.
IC-8-152	Hematite ore	Ore minerals recognized in this section are large amount of hematite and magnetite with small amount of chalcopyrite and bornite, although slight amounts of sphalerite and Pb-As series (?) minerals are recognized. Chal- copyrite is associated with bornite and they are recognized to be dissemi- nated or in porphyritic texture. Sphalerite includes dots of chalcopyrite partly, and is included in chalcopyrite. Pb-As series (?) minerals are found included in bornite and along boundaries between chalcopyrite and bornite. It is possible that these minerals of Pb-As series (?) would belong to minerals of Pb-Bi series or Pb-Sb series. Hematite is recognized to occur in needel-like crystals, in forms of dissemination or aggregation. Magnetite is found to occur around hematite (see photograph).
IC-8-161	Hematite ore	Ore minerals recognized in this section are large amount of hematitc with slight amount of chalcopyrite, bornite and sphalerite. Hematite is found to occur in needle-like crystals. Chalcopyrite is found to be asso- ciated with bornite in some cases, while it is associated with sphalerite in other cases.
IC-8-163	Py siliceous ore	Ore minerals recognized in this section are large amount of chalcopyrite, pyrite, magnetite, hematite and slight amount of arsenopyrite. Chalcopy- rite is found to be disseminated or to occur around pyrite. Pyrite is euhedral in many occasions. Magnetite and hematite are also recognized around chalcopyrite. Accordingly, it is thought that the order of crystal- lization would have been chalcopyrite + pyrite + magnetite + hematite.
10-8-167	Py massive ore	Ore minerals recognized in this section are very large amount of pyrite and slight amount of chalcopyrite with very slight amount of sphalerite and ezurite. Pyrite is found to be massive. Chalcopyrite and sphalerite are fine grained and are recognized to be contained in pyrite. Azurite is also found to be included in pyrite.
IC-8-170	Py diss. ore	Ore minerals recognized in this section are large amount of pyrite and small amount of hematite and sphalerite with slight amount of chalcopy- rite. Chalcopyrite is euhedral and is found to be disseminated or in porphyritic texture. Sphalerite is recognized to contain dots of chal- copyrite in parts, and is found to occur in and around pyrite. Chalcopy- rite is also found in and around pyrite.
IC-8-177	Cu-Spc ore	Ore minerals recognized in this section are large amount of magnetite and hematite with slight amount of chalcopyrite. Magnetite is recognized in characteristic succaroidal form which seems to have replaced parts of cer- tain gangue minerals, while hematite is found to occur in needel-like crystals. Chalcopyrite is recognized to be scatteringly disseminated in gangues.
IC-8-178	Py ore	Ore minerals recognized in this section are small amount of pyrite and slight amount of hematite and chalcopyrite with very slight amount of sphalerite. Pyrite is euhedral and is recognized to occur in seams or disseminated. Chalcopyrite is found in veinlets and in dots contained in pyrite. Sphalerite is found to occur in dots contained in pyrite.

		(3)
Sample No.	Rock Type	Microscopic Observations
CN-5-20	Dolomite	Ore minerals recognized in this section are small amount of sphalerite and very small amount of pyrrhotite, marcasite (?) and graphite-like mi- neral. Sphalerite is found to be fine grained (under 100 µm) and is recognized to be scatteringly disseminated. Only one grain of pyrrhotite has been recognized, in this section, which is associated with marcasite(?).
CN-6-24	Altered rock (Py diss.)	Ore minerals recognized in this section are large amount of pyrite and slight amount of hematite, chalcopyrite and sphalerite with very slight amount of galena. Pyrite is found to be massive or in porphyritic texture. Chalcopyrite, galena and hematite are fine grained and are recognized to be contained in pyrite. Sphalerite is found to be fine grained (under 100 µm) and is recognized to be associated with gangue minerals.
CN-7-17	Py massive ore	Ore minerals recognized in this section are very large amount of pyrite and slight amount of sphalerite, chalcopyrite, azurite and phrrhotite (?). Pyrite is found to be massive. Other minerals as sphalerite (including no dots of chalcopyrite), chalcopyrite, azurite and pyrrhotite (?) are re- cognized to occur in dots contained in pyrite.
CN-7-24	Zn-Spc ore	Ore minerals recognized in this section are very large amount of sphalerite and small amount of hematite with slight amount of chalcopyrite and galena. Sphalerite contains dots of chalcopyrite in parts, and is recognized to be massive. Hematite is found to occur in needle-like crystals and is found to be contained in sphalerite. Chalcopyrite is recognized to be in dots included in sphalerite. Galena is also recognized to occur in dots con- tained in sphalerite.
CN-7-26	Zn diss. ore	Ore minerals recognized in this section are large amount of sphalerite and pyrite with slight amount of galena and chalcopyrite. Sphalerite contains dots of chalcopyrite in parts and is recognized to be in porphyritic tex- ture or in form of dissemination. Pyrite is euhedral and is recognized to be disseminated in and around sphalerite as well as in gangues. Galena is recognized to be in diameter of 500 µm to several 10 µm, included in sphalerite. Chalcopyrite is recognized to occur in dots contained in sphalerite. It is characteristic in this specimen that pyrite is found to occur surrounding sphalerite, and it is thought that the order of the crystallization would have been sphalerite + pyrite (see photograph).
CN-7-28	Zn drusy ore	Ore minerals recognized in this section are very large amount of sphale- rite and small amount of pyrite with slight amount of galena and chalcopy- rite. Sphalerite contains dots of chalcopyrite in parts and is recognized to exist in porphyritic texture. Pyrite is euhedral - anhedral and is found to be contained in sphalerite. Galena and chalcopyrite are recog- nized to occur in dots included in sphalerite.
CN-7-29	Zn - Py ore	Ore minerals recognized in this section are very large amount of pyrite and small amount of sphalerite with slight amount of chalcopyrite. Pyrite is recognized to be in porphyritic texture and in form of dissemination. Sphalerite contains dots of chalcopyrite and is recognized to occur sur- rounding pyrite and filling spaces among pyrite grains. Chalcopyrite is found to occur in dots contained in sphalerite.
CN-7-31	Zn-Py ore	Ore minerals recognized in this section are very large amount of pyrite and small amount of sphalerite with slight amount of chalcopyrite and pyrrhotite (?). Pyrite is found to be massive. Sphalerite contains dots of chalcopyrite in parts, and is recognized to occur in and around pyrite. Chalcopyrite is found to be in dots contained in sphalerite. Pyrrhotite is recognized to be in dots contained in pyrite. It is noted that pyrite has been marcasitized as a whole.
CN-7-33	Zn-Py ore	Ore minerals recognized in this section are large amount of pyrite and sphalerite with slight amount of chalcopyrite, thought very slight amount of galena is recognized. Sphalerite contains dots of chalcopyrite in very small parts, and is found to be associated with pyrite. Chalcopyrite is recognized to be in dots contained in sphalerite. Galena is in diameter of 20 - 30 µm and is found to be contained in sphalerite, though no more than 2 or 3 grains of galena are recognized.
CN-7-35	Zn-Py ore	Ore minerals recognized in this section are large amount of pyrite and sphalerite with slight amount of chalcopyrite and galena. Sphalerite contains dots of chalcopyrite partly and is recognized to occur surround- ing pyrite and filling spaces among pyrite grains. Chalcopyrite is re- cognized to be in dots contained in sphalerite. Galena is found in a diameter of several 10 µm and contained in sphalerite (see photograph).
Law I		


(3)

.

.




A - 31



Sample No. IC-8-152(2) Type of Ore : Cp-Mg-Hm Ore


Cp : chalcopyrite Mg : magnetite

- Hm : hematite
- G : gangue minerals



Sample No. CN-7-26 Type of Ore : Sp-Py Ore

> Sp : sphalerite Py : pyrite



Sample No. CN-7-35 Type of Ore : Sp-Py Ore

M	inerals	N	te	ite	Ĺťe	ite	Mn-Siderite	te	Pyrophyllite		ite	lte	u		ße	erite	e	Chalcopyrite	Smithsonite	Plumbogumnite	Pyromorphite	-	otite	ite	Remarks
Sample No.	Туре	Quartz	Calcite	Ankerite	Dolomite	Siderite	Mn-Sic	Biotite	Pyropl	Talc	Chlorite	Sericite	Gypsum	Rutile	Anatase	Sphalerite	Galena	Chalco	Smiths	Plumbo	Руготс	Pyrite	Pyrrhotite	Magnetite	
IC-6-181	Gyp-v	0					•						0												
IC-6-185	Sid						Ø															•	0		
IC-6-194	Sid-v	•					0									•						•			
IC-7-106	Ss	0										0			•							•			
IC-7-136	Do	0	o	0												•	•								
IC-7-146	Py-drs	0																				0			
IC-7-209	Do-v	0	Ø		0																				
IC-8-026	Sh	Ø							0			•		•											
IC-8-133	Py-ore	٥																•			•	0			
IC-8-152	Ald	0			•	•		•		0	•					0		0	0						
CN-5-15	Wht-v	0														0	•								Cly-ms
CN-5-20	Do	0		0						•	•					•	•						1		
CN-6-30	Ald	0			1						0											0			
CN-7-21	Ald	0																				0			
CN-7-31	Sp-ore	•														 0						0			

A. II-5 Summary of X-Ray Diffraction Analysis

A - 33

Ald: altered rock and gangue minerals in ore v: vein drs: druse


💩 abundant

O common

• fairly

• rare

A. II-6 X-Ray Diffraction Chart (1)



A. II-6 X-Ray Diffraction Chart (2)

01			
	8	×	
		м	
		2	
والسنيشية وتعاريا المتعارية المتناع والمتناع والمتعادية والمتعادية والمتعادية والمتعادية			n
<u>n an an san san an an</u> an	(BRORUE), BRUTHER UTTER KOTT UTER URER DETER DETER DET VERTER DETER DETER DETER DETER DETER DETER DETER DETER D	YAN TARA DATA BADA YANG ARTA ARTA TARA DATA BADA DATA DATA BADA DATA BADA	TERE CERTIFIC CONTRACTOR DEPARTMENTS AND A DEPAR

Sample No	IC-6-181
Target	Cu
G.Monochro Voitage	40 kv
Current	150 mA
Full Scale Range	4000 cps 05 sec
Scanning Speed	4 °∕min
Chart Speed Divargency	4 cm√min 1 ●
Receiving Slit	0,15 mm
Detector Date	S.C 3 1984
Diffractometer	0.000
Rol	aflex RU-200


MINDECO

Sample No IC-6-185

Target	Cu
G, Monochro	
Voltage	40 kv
Current	150 mA
Full Scale Range	4000 cps
Time Constant	0.5 Sec
Scanning Speed	4 */min
Chart Speed	4 cm/min
Divargency	1 •
Receiving Slit	0,15 mm
Detector	SC
Date	3 1984
Diffractometer	
Rotaf	lex RU-200

MINDECO

A. II-6 X-Ray Diffraction Chart (3)



A. II-6 X-Ray Diffraction Chart (4)

	197-11			1-1-1	Ŧ	r T	1 ::	<u> </u>		T											199							Sample No	10-8-152
			"	-							30					×					10							Target	Cu
-	-		-		" ; 	· ·																						G.Monochro Voltage Current	40 kv 150 mA
+						1 0- 					89-										×				. 10			Full Scale Range Time Constant	4000 cps 0.5 sec 4 */min
i	1 	**************************************				,					-10-1					70												Scanning Speed Chart Speed	4 cm/min
	-	-					-		-																			Divargency Receiving Slit Detector	1 • 015 mm SC
 	00					8:1 ⊦- ⊷1		1			a q									1,41144			:::::::::::::::::::::::::::::::::::::::	;;;;;;; ;;, ; ;				Date	3 1984
						89-1 ,										4									•			Rotafi	iex RU-200
			-																±i⊷ht+ith										MINDECO
											1.44										99 8								
	19 B				<u></u>	N				, HE	· * 1			11 2 11	42 44							64.44	II: THE		NC K				
			ortice -												l in		8	8				8							
W.	will-		đ			- 		1 1				N-					3					V		A					
		<u> </u>	<u>ا سبا</u>	Marine 1	المتياسه								7 V		T.V							(¥			- (L)A	<u>, 1 V</u>	///w		
•	± 1			-																	•								
	-+	10			╴┽─-∲ ╌╶╉─╶┿		_20			╺╴╺╄╼ ┎╶╾╉╍			••••••••••••••••••••••••••••••••••••••					0			71117-1	5	1 1						

.

Sample No. IC-7-136

Target	Cu
G, Monochro	
Voltage	40 kv
Current	150 mA
Full Scale Range	4000 CPS
Time Constant	0,5 sec
Scanning Speed	4 /min
Chart Speed	4 cm/min
Divargency	1 •
Receiving Slit	0,15 mm
Detector	sc
Date	3 1984
Diffractometer	
Rotat	iex RU-200

MINDECO

. . .

A. I-6 X-Ray Diffraction Chart (5)

	100 It //
	arte tala pe sa seat pa set e trans futent baba t sa bei sa se
	<u></u>
	<u> </u>
	• • • • • • • • • • • • • • • • • • •
	······································
	· · · · · · · · · · · · · · · · · · ·
	· · · · · · · · · · · · · · · · · · ·
	
- LE B. T. L. L. L. C. STATTA BARANA AND STATTA BARANA AND STATTA STATTA STATTA STATTA STATTA STATTA STATTA STAT	
╶╴╡╶┊╴┽╶┼╾╺┽╴╎╶╄╌╫┥╶┊╶╎╴╎╴╎╴╎╸╎╉╞╢╴╡╶┥╍╠┅┥┥╭╞╍╴╡╍┽╍╘╌┉┼╫╪╭╓┦╍┥╢╢╴╢╵╘╎╢╍╢╷╡╖┽╌╗╢╌╫╢╢╢╷┼╠╎╴┼╓╢╶╫╵╢╵╢╎╢╝╝	
二十二编 医丁丁二氏二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十	
╡╪╪╪╪╪╪┿┿╖╖╗╗┙╗╗┙╗╗┙╗╗╋╋╗┙┙╝╋╋╗┙┙╝╋╋╗┙┙╝╝╗┙╝╗╝╝╝╝╗╝╝╝╝╝╝╝╝	
	하는 것 같은 것 같
	31
	X////
	الاستهدية المستعلم المستعل الم
	╘╌┼╍┟╍╂╸╂╴┟╍┨╴╁╍╄┷┷

-- **-**-

.


(

l

,-

•

A. II-6 X-Ray Diffraction Chart (6)



Target	Cu
G. Monochro	1
Voltage	40 kv
Current	150 MA
Full Scale Range	4000 CPS
Time Constant	0,5 Sec
Scanning Speed	4 */min
Chart Speed	4 cm/min
Divargency	1 •
Receiving Slit	0,15 mm
Detector	SC
Date	3 1984
Diffractometer	5
Rotal	lex RU-200

Sample No. CN-5-20

MINDECO

Sample No CN-6-30

	· · · · · · · · · · · · · · · · · · ·
Target	Cu
G. Monochro	
Voltage	40 kv
Current	150 mA
Full Scale Range	4000 cps
Time Constant	0,5 Sec
Scanning Speed	∠ */min
Chart Speed	4 cm/min
Divargency	1 •
Receiving Slit	015 mm
Detector	SC
Date	3 1984
	3 1504
Diffractometer	
Rota	lex RU-200

MINDECO



LIST OF PLATES

`-, --=`


13 at 11

f a

PL. 1	Exploration Map of the Limpe Area	
	Showing the Drilling and Tunnelling Sites	1 = 2,000
PL 2	Summarized Projective Map of the Drilling Results	1 = 2,000
PL. 3	Summarized Projective Section of the Drilling Results	1 = 2,000
PL. 4	Inferred Geological Map on 4,690 m and 4,570 m Levels	1 ≑`2,000
PL. 1-6	Geologic Drill Log, IC-6	1 = 200
PL 1-7	Geologic Drill Log, IC-7	1 = 200
PL I-8	Geologic Drill Log, IC-8	1 = 200
PL. 1-9	Geologic Drill Log, IC-9	l = 200
PL. 11-11	Surveying Map of Exploration Tunnel, Adit-N	I = 500
PL 11-1-2	Surveying Map of Exploration Tunnel, Adit-S (1)	1 = 500
PL 11-1-3	Surveying Map of Exploration Tunnel, Adit-S (2)	1 = 500
PL 11-2-1	Surveying Map Showing Location and Level of	
PL 11-2-2	Exploration Tunnel, Adit-N Surveying Map Showing Location and Level of Exploration Tunnel, Adit-S	1 = 1,000 1 = 1,000
PL 11-3-3	Geological Sketch, Adit-N (3)	l = 200
PL 1134	Geological Sketch, Adit-N (4)	
PL_ 11-3-5	Geological Sketch, Adit-N (S)	1 = 200 1 = 200
PL 11-4-2	Geological Sketch, Adit-S (2)	1 = 200 1 = 200
PL 11-4-3	Geological Sketch, Adit-S (3)	1 = 200
PL. 11-4-4	Geological Sketch, Adit-S (4)	1 - 200


51 / (

٢¥





1 af

<u>.</u>




المراجع المراجع






]	(PHASE D) GEOLOGICAL SURVEY PL. 3
	IPBOSSIU GEOLOGICAL SURVEY PL. 3 OF THE ISCAYCRUZ AREA, PERU
	EXPLORATION PROGRAM OF THE LIMPE AREA
	SUMMARIZED PROJECTIVE SECTION
	OF THE DRILLING RESULTS
>	Scole I 12,000
	WETAL MINING AGENCY OF JAFAN JAPAN INTERNATIONAL COOFERATION AGENCY
	AFRIL 1934
	Prepared by MINSECO
	LEGEND and ABBREVIATION
	Fb-Za k-g-g-52e ore
	Fb-Za ke-gole at
	Ce se
	Washe Pythe ore (Py)
	Missive Parafile cre (Rm)
	Cr Color Fordia
	St Sovie Formation
1	Ca Chirs Faristice
SE	U Upper korizoa M Mikste korizoa
	L Lever koriza
47X p	
45× 11	
946 (<u>1987</u>	
45:0 .	
44.2.8	
43.Cu	
1	



.....


GE IS	OL. CA	00 YC	iic RU	D Ž	RILI PRO	L I)JE	.00 CT	. 0	ordi: Ievo		ε.	308,6 310,5 4,69,		
· · · ·		ays T			₫h Sy			<u>ب</u>		<u> </u>	г	r—	Observations	Assays DepthSymbol Occurrence Observations
1 2 2 2 2 2 2	3	12	<u>11.</u> 5	े 6	18	511 (µ) 9		01 11	•					$\begin{array}{c} reg (re \ Fb \ Ze \ A1 \ Co \ Ce \ Ser \ Vol \ Co \ Ser \ Vol \ Ser \ Vol \ Co \ Ser \ Vol \ Ser \ Vol \ Ser \ Vol \ Ser \ $
	Γ	Γ						1.0		1				10 000 005 2 3 4
									34					15 002 027 141 4 15 003 002 150 H 15 003 002 150 H 15 020 002 361 H 15 020 002 361 H 15 020 002 361 H
				•			54 (55)			84	61		Surdy Sa, physica	
1	1					<i>8</i>				<u> </u>				12 003 003 003 007 100 110 000 - 270 - 10 10 10 10 10 10 10 10 10 10 10 10 10
				19 1			() (54)	_		 	1-#1 ~~~	-	Egt, knira	13 052 002 29 0 4 0000 1553 51 05 be Margan tenset
							54			P _f	1		Sordy st	15 055 001 505 44 XX 15
				176		зf	5,			P.,	97			14 453 091 030 4
.	<u> </u>			ŧ.4			0-1 	<u> </u>						25 053 002 030 4
				222			<u>\$</u>	-		P)	**		¥m Ss prickes	
					•••		92 651			3			₩35- 1 <u>5</u> 8	36 C < 3 C 072 O 20 H5
													271-273: 56.	
		 	-	x			 		 	 				(3 ² 23 ⁰ 00 ¹ 00 ⁶ 8
							54			PI	11		Transford and Physic, Boly	
						ъſ						·	33 4 - 345 : debaile 34 7 - 365 : eg	55 (02) (00) (6 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
				æ			53]—	Cy.]	2 11			By CY By 6-pt Py Refer we
		 		天1 40			A.1						379-323 : F+ Cy All 155 - Sil	
				æ 3	—		·	<u> </u>	<u> </u>					
				4		ವ	62]	51		632,633,63 xY-14,45, 02:0	50 100 003 070 20 51 Cg Py 635 is a V (cy out.
							62	الم		n			tares con J	Core restry is to
	ĺ													50°0 8°009'008 12
				50						1				
				5 23	1		23	┝		Py.			A7 154 - De - Se	50° 3° 012 003 36 1 152 5 - 152 8 ; Ha.
		İ		¥.` ¥≁		35	Sa		c'y St			*		
							W 1 1593		4		¦.,,		Very sat	50 024 001 050 1/2 07 1/2 1/2 1/2 1/2 0/2 0/2 0/2 0/2 0/2 0/2 0/2 0/2 0/2 0
		ł		દ	F.		 50					·	torice of \$3.8 with	
			ļ	~			5	-	-	┝	97 97	-		- Forty restrict to
		Į		64		55	·V1							to the second se
						-	C+			5	••		Fed, cryst Bestone sh	U 005 001 135 12 87 127 47 47 47 48 54 54 725 497 850 - 511 54 853 1 639 1
	-			ĸ	677		 52		·		 			
			ŀ	715	罚			┢─			1 77	-		
														A1 (Co S)
						÷			1					
	 			8.									· • • • • • • • • • • • • • • • • • • •	
		1			行			ļ	l					13 004 002:331 4 17 7 54 120 72 54 120 72 54 120 74
				B	臣		_							is craces and a line of the contract of the co
							55 Oct		4		81		føt, dokate	3 CO 03 331 1 a 2 10 10 1 1 15 12 15 10
	1			30]			802-835- SA	0-20-80 ce 24
											1			
5 00	_ _			×					 	 	 	_	930-934. St Co-Fa	Ad Free-A1 (De-53) 0-20-80 (e internet) 6 002 (cs) (cs) 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
1.2			T 👝	×			L1 	_	(Y 	Py So	[<u>n</u>	54	Az (Sa Dal) Sr-fm	3 (00) (00) (160) (2 3 (0)
2002			4				<u>6</u> .04	í	33	7) 50	(en		28 2 55 64 (Decole Ss) Sch ogd Ac 42 003 Ca5 527 4	
<u> </u>			<u> </u>			ι	.	۱	L	ł	<u>ـــــ</u>	L[15,002,002 (60) 4 [[15] 54 [15] 54 [15] ZOJA #6



LEGEND and ABBREVIATION

ю	Fizek	Pettle, soid, do	1 Feb	(7 T)
		Sadstare	Si Si	
		Sicle	Sh.	<u></u>
		Val	N I	
		Linesse	 Ls	
		Diorite Ereston		
		Doostore	Co - Co - Co	<u></u>
		Scerie	54	무무귀
		Quartzite	3-9 (71	6.6.4
		-		
		Ore, Ligh grote		
		Ore, ka giote		
		Parite ore	Py	
		Perchite ore	5m	L'L'
		Segan	St	<u></u>
		Beccic'ed rock	6-c	· · · · · ·
		kteris rock	A	
		Fort, Rectore	F	
11.	Criccica -	61.6761	61	
		Executives	5 3	
12	Ateration	6-ce:122-14	60	
		66°0%20*00	(cl	
		679772676A 510766-64	e'y s-1	
		sericitization	5.5	
		30.70110.07	•••	
13	Mresizzoa:	Pyrite Pi	00000	ie Cp
		Frances Fr		
		Ze a recs Z		Fas Spc
		Orice aires's O	id Vogretike	¥1
14 .	Celer :	1.31/1	- 8'002	13
		in e		n ¹ 4
		413 G	u brown	tra .
		F -	-	
- O	Erodure 1	िद्धी इन्हेल्सी	F 574	
		weres weres	50 1/1	
			~ ~ ~	
76	Orentas	l succession	¢ 55	
		VEITS	τ5	
		Be's'ets	¥*5	

Assoys		lh Snb				nce	- -	Observations		Assoy			hSynt			ccurre			<u> </u>		Ass	oys	De	phSyn	nbol	Ó	ceurre	ence	·	I
6 A 7 4 N N N 4 2 3 4 5	1		≠×*	0.8	<u></u>	<u>(1</u> (7	× 1 ma		170 C		29 A9		3-15	4	1 611	Ait	N.) (4	Figel	Observations										Ceior Frant 14 15	Observations
	Ť	<u>[.</u>	1 1						1 2		4 5	6	<u>(*8)</u> [- [- [-	3 14					16	Ť	2 3	4	5 6	78			12		· •	16
			ľ,	<u>م</u>	51 I	Py ¥	1	¥94						11. 1. 1			Py 29		642				120			5 6		_		1
												~ ~		* 6		-			Cryst. soft cryst lad							Cap	\$5	9,2	9"J	
												æ		51	-†		Py > 1		Abrediel Q'é sur far at \$1 X my Fige EQCel		002 04	260.84	-							265-2078: Sd. Py Za 6
	18		55									чc				ļ.,			.695-3023.St. Std											Cal - Do -Ol casenbloge is defermined by Ximy 203a
	e ,		<u>53</u>	[_['	°, [6:3 	"1	Sa ⊯ta Sa				11						Í	HI3: 59-7. 05. 55.		1		æ	臣			1-1		- 97	¢α*α π∶rêt by X rêş (203a
			<i>∽</i> 1		53 J	7 ھ 1-9		Fgd - # 3d			1											_	_ 24	별			_		•M	
												1-55	W W	Сс 54					Paras Sa, cel-10/3 ara	0		2 C55 33 O36 2 CC8 2 CC8 2 C25 33 Q20 33 Q20 33 Q20 33 Q20 33 Q20 33 Q20 33 Q20	- 26	9		n Du R	- - 60 	P)	· -	-
	- 7	· · · · · · · · ·						Free 193: Or 21 Sa Bia Less				125		ج		$\left \cdot \right $			1403×5	10	003 00	02 025				Dre				
			9		1	7 y		So with So policites, peticies, B beca				22:		<u>ک</u> کے		 	•		Ca-fa	0	00300	5 0 2	220	12			f i f			
	æ.:	١.]]		_		_							0	<u>' </u>	4	(-) •	1 . 1	220-034: Cy St-Fa	<u>10</u>	00000	2 0 20	- 23		-	53	+			1:10, 10 Do
	7:-	<u> </u>	. ∾		'	Pg 81	•	Monsive stay Do						- 10	. ta	9		7				╺┨╌╂	_			Ce3			61 54 61	, 14°C, 18°B (10
		[:]	Or	Ī	53	² 3 13	,	the arts states				₹ŝ			1-	5		1,01		-		┤╏	-		1					ļ
	1×		53 53					55 x 3 Sa		· • · ·		105	盟		- 		•			-		╉╍╉	- 🕅	圜			60		*1	
	2		38 01			7 19																11	- 22			Ls -	601		+71	Cel 15
	Æ	36			5 I F	, j ,	, 	Fyt					雳	E.	-	c.7										Da	*		¥1	Co 13
] []	ĺ	*	ł				3.000		32.3	阙	0	1			1 5.0	On is described by Froy (Keal				39.		x	5.	-		12 54	
	- E	苎	<u>54</u> 62					The Karata	20,00		- 1			- 24	×{		54	L	••••				- 20							· · · · · · · · · · · · · · · · · · ·
		· · ·			87 1 54 1	Py 1.3	Ί	9°6 3 κ₩8	23.64	.e.cc.	- 13 -		1								·				ļ					2250. 00
			4	_[58	F, L		A.C. (See Co. WI-Ss)	20 0	11 OCS (- 63																		ľ	
					5	Ĭ,	1	Se is precedent	1-1-			-I 14			1				Py -O contra is dissified by X-ray (145a)			11								
- -	- 50	- S				{		-438-505 : \$s. 513-524 : Sr	20.0	:5'003' 		- 150	4			5 7								<u> </u>						
		93.4 										- 24	4	54	Ţ		2 4													
	¥	.					.	550 - Paracta 551 - 557 : De	╵╏╂	+	- -	-	2	Ĺ	1	5 7														J
	×		01	. La		y 81 y 1.9		fat-sat					N A						Duses Nos core											
	60				5er -							60	<u>VI</u>														1			
																							250							····
																														ļ
																						ľ				ļ		1		
			54		c1	·		54 × 51 Ca \$ 5a	28 6-1	3004	:90 b			64		4	4.	2												
	7=		55			_	54					1×		τ,					F2f 522-15 & 263-23			• • • • •	- 70) 						
	7	哥	,, ,			-†-	-1																							ł
		H			() 	Ì		あち- 78つ: 514											1755-1558 t sta						1					
		÷.							<u></u>				R																	
	- 80 8.1		1543 07		<u> </u>							8	E.				· · · · · · · · · · · · · · · · · · ·		65-13 8 ceret	•-			25							
	s	强	VI.		*7			Very soft			Í	8	B	`[₃	[[]			1		ſ		Ì		Í			Í
		圕									į		围	¥1	1	-	± ,	2	Co≿, fgi											
		盟"										f	틪	5		╞═┼	- 18-3		Pay te											
••••••	. s							¥cs		<u>. . </u>		æ	<u>}</u>		<u>.</u>				Desale La]					
				I	ļ			-						L.		2														
												*	斟		- -	$\left - \right $	-		644-641. S. 2.5 tel											
			58	ļ		_ !						X 4	罿	17	1	11-	- 1-0	, , ,	1 I			11		11	1	1	1		1	1




LEGEND and ABBREVIATION

n	Back	Pett'e, soid,	-'r •	Feb	
· •		Sordstore	,	55	
		St.c'e		55	
		Vor1		on. ₩i	
					時時間
		Lices's e		15	HTTE
		Octomite three		Dorls	<u> </u>
		Colosione		Do	
		Siderie		54	1.1.1
		Quorizite		Q12	<u></u>
		Ore, Ligh gri	ice -		de to
		Ore, ha go	×.•		
		Pyrie cre		Py	
		Heretite are		Fa	1.2013
		\$120		Sk	<u> </u>
		ઉલ્લંદ'લ જ	Ł	E-c	<u>[</u>]
		Attend rock		A	
		Feel, tractore		F	1.1
				-	
П.	Oričetka i	ex:6283		C+3	
		Locificed		1.5	
12	Ateston	ecolor in a state of a		¢)	
		cciotize"-on		cel	
		erg Eiseten		¢7	
		STC FCCTOR		s-1	
		seriestation		\$4:	
13.	Kreston:	Prite	Py 👘	Occup 1	L Cp
		FE- # 1 6:03	F2	O cicco te	Ce
		ZR-RILEIGS	Za -	FET C. C	Fa Sc
		Olde ellers	03	Vogere	¥1
₩.	Cover	t gal	• • •	block	th:
		652	e -	a v e	**1
		91) (71)	\$ 7 1	Draw V	tea.
S .	Froduce :	Feat		F	
		ちをいそう		\$3	
		breccic es		tre .	
26	Observations :	disseries for		655	
		NE DS		13	
		88 8 ETS		¥ 5	

G I	EO SC	LO :AY	GI CR	C	Df Z	RILI PR	L L OJ	.00 EC1	r۷	oordie te vol	iole tion	н <u>в</u> Е	808 3 0 9 1 5 7	DDH No. 1 C-8 112 Direction _250 24 Inctrotion _30 ⁴ 3m Total Cepth _2028m														
		50)		_		th Sy			00	cur	reno	æ		Observations		Ass	ays		Depl	hSyn	bol		000	CUILL	ence	;		
	<u>%</u>	2		d,	3	1/8	Ste (a)				¥A.			Observorions		12 P		23		द्भ	Sr.	R.a.	0.1	A.11	22	(o'y	Frad	Observations
-	5	3	•	5	<u>ہ</u>	1/8	9	10	11	12	13	14	45	16	Ī	2	4	5	6	/3	9	10	11	12	13	(4	15	16
								¢1	Į	10	8,	6 97 9		Gry spots in whit extra				j .				A'4		Ċ0	J	\$1		¥196 Se 8 Se
								1		[~				rgd, stry bord					627 635	\ge								Fruste fice out unter, 600fmin,
		Ì	Í																	·		£4		1		\$1		KARING E. PH 2-1
						<u></u> }					1			80-97: 64, 50					σ_{i}		3			<u> </u> Į				
					r,									. 99 : Parte		_			12	Ĩ,	5	<u>sa</u>	1	<i>ci</i>	_		5 I	- 653+ 663 ++ 56; <i>-#3_09+-</i> +
11					1	::			1		ł				43	075 07	M_000	-		1		30		92 C3	P,	je i		
										ļ										1								
						{ :					Į				43	004,00	0.05			<i>:</i> .	đ				ļ			
								ļ						173 Py-65 629 J						1			ļ					
					20	[∵	Ì	.	.	.	ĺ	.					Ĩ		183	\mathbb{Z}		794		~				- 23. 9569. 52.
		Í			20		5	I	Í						45	oos oo	2 ⁷⁰⁰⁷	-										
							5	55			84	6-m		Sondy-Shi, decedie	·			-										
											10.		į	Prophysia - 2000 Concerns by X-cop (2001	65	စာေတ	× 008	-		$\langle \rangle$								
					2		5						Į	266: Py 2cm 5			4_	 _		1			Ì					
								6.5	i		R.			258: Pj-144		004,00	2,005	*		1								
					32			,	[3 .	 	1-972							135	1			···	•	···			·
						$ \cdot \cdot$													вd	\overline{Z}		3.00	Í	51	P,	pe!	Ì—I	87 6 1559 00
		İ				5	5	55	<u> </u>		6	⊦n			33	œ₄'œ	2001	1		1				57				Py Of essentiate & contract
					X X		•5			-		ЬЪ		9 m 5		0.6.0			55	• •					F,			ty K-ny (*3351) Py N-der pre
	ļ	1	1	1				51			P,	81	Ì			Ĩ		<u> </u>								~		
			•••	• • •	~			ζm)			l				51		2,026	¥.	нc			· • - ·						
			Ì					ļ								_		⊢										
	i			Į				1			ļ				32	005 ¹ 0	×1003	- 1		1								
			Į	}			Í.	ļ]	ļ								╞		11								
															32	~~`~	× 0 0	Ē										
					50						 	• •			22	005 0	0.03	•	53		5	Rđ		611 СУ		9- yr		
					51		5	55				Y,			- 0	024 (X) C37 (X)	ອີດກ			$\overline{\prime}$		or Syx Ore				¢-7,	1	
				l				Q2				1-grg			12	0.50	2 655	Ē							\$×			Ar 35 650 662 653 W
				ł	52			54	}	07	[Californias Locination is developed	28	0 2 X	2 2 45	-		•	5	14			S.z	¢-73		544: Cp-255
				ļ	Š				<u> </u>	3		гя. Г		568: F-cy		007.00				Ĺ,				× e	-			Sp-Tele-Gt energies is Generated by Regulated
					60		[¢'1		51 557	 	t-γ-) >≥	 	585: Frey			-	Ē	54. X									592-598: cy. F. 70
					6 1			<u> </u>	[<u> </u>					45	253 0	2,033	•>				ΕA		c'y dvi	Р. Р.	+ 37		· · · · · · · · · · · · · · · · · · ·
					<u>6</u>		5	58 1721				*7								• •								
								0.			۱.	24		Lin citry J	30	020	ж. са	ke	<u>ן ז</u>	1		Proe	_	53	Py .	рe		Py mossive are
							Į			5-8°	Ľ			· · == # =	-			-		1				1				
			ŀ				Í								23	609 CO		<u>ا</u>		1								
					£			54	╞	[714-734: Cy tets	35	032_0	× 655	1	Ŕ			24		• 7		5 - 5 - 3		
					23			53		1.7	1			and the spaces				1	53		న	รับ			ካ		Ļ	
			ļ		ъ:		5	55			F				13 13	007 I 074 C	2 008	4				502 - 0 1		CY ST	Syc Ca	1.1		Theat
							5	53	ĺ	4	67	8-99		int my terre	12	00 C	2 003					4-540 01			· · · ·	**		H & & & A & A
	Ì							(9)		1	1			Fs parcifet la tetting 1792 - 8:0.		0.000	-	1	6	<u>///</u>		41	-	ei.	7.0		<u>+</u> _	L \$30-€07: \$*4
		- t			æ		3		 • •	····	1	••••							×	<i>.</i>		1573		3	6	-ú.	· 24	-
			Í		- 1		[ĺ	[[Í	ĺ			~~ o		<u> </u>		- 1	5						1	Loning & resolution
	1				£C.3			\$s		5.7	P.				17 	001 0. 	ж'сез - Ц —	1-	£	A A 								St-Fm
		1				200 12	ত	C*2 1			Ĺ	_					Ì	1				54	ļ	51		(-y) 121		Lunca (2-fo
																										Ļ	 	
			· · į .	-	¥			 	 	 	<u> </u>		 	•••••				1	إمر		3	ж.		. 01 51	₽g.	- 779	1	
								55		<u> </u>	"	¢-37)	~						1 1	뮲				5				
					Ţ			\$1 \$21					ļ	Cu-Fa				[341	臣		 Ls				1.57	ţ	
					3.1		Ś	Co		11 41	[81	[950-954: sha Box boy is torstand			ļ											
					5	R.	Ş	L9	 		1	*7	[Box 2017 is forst and St-Fa				1	3.4		5	Sa		—		C-37	1	torna
J				_	39	F	<u> </u>	līī	<u></u>	<u>;</u>	<u>†</u>	E	1	Drise				1	₩			55				• * *		Fys

يعينه المكرمة الماذية ومنهمة مدارية وتلائه تراز مراد تعل مدار مان تشار


	A	\$50	ys		De,	th9	ntoł		Q¢.	ourr	ence	•		
-	8	ŝ	お	4	040 (13)	7'8	523	Fict	C+1	**		(++	Fract	Observations
E	2	3	4	5	8	1'8	9	ю	Π	12	13	H	15	16
1								5.				\$*I		
			Į,					58	i –		2,	12		2028a. e.t
												[EVE 03. E-7
												1		
1														
• •			• • •	• •	2-0			•						
			ĺ	[[í							
											•			
ļ								ł						
-					220	.							l	
1														
												1		
			}									ļ		
			Į	l				1	Í					
			1	i	1	1	1	1			1	1		



LEGEND and ABBREVIATION

10. Rock	Petble, sold, day	Peb 💦
	Sundstone	Ss Etter
	State	Sh 🗮
	Vort	MI DEED
	Lines we	Ls BBB
	Ocionatic Insteadore	0o-Ls (2523
	Doksfore	0.
	Sicerite	Sa 222
	Questzite	84
	Ore, Eigh groce	
	Ore, ica grote	
	Parte ore	8 22
	Reportie ore	8 7/1
	Size	S []
	Breccipies upok	6-
	Attend cock	
	Four freeture	
II. Cuzetica :	CR d red	C*3
	I for fized	link
12 Aterction	6000.T201-00	63
	00 05 10 00	133
	Croit zer co	C J
	STOTECTOR	5-1
	SETCITIC	ser
13 Vietizion	Pyrite Py	Ociaigante (p
	Po-rate os Fo	Occession Ce
	Ze alteros Ze	Fercile Fax Spe
	Orde evers Od	Vogretike VI
H Ceser :	foht - E-	
A 160.	ight t- Cork d-	1/000 2/2 1/2/10
	જરૂર જરૂ	bran bra
	., .,	•••
S. Frontie :	Feal	F
	step ed	\$*3
	percicies	trc
is according	6 55-57-57-57-57	ð 55
	10115	15
	se's'els	**5


550	ys z. L	Dec	thSyn cal J	8		CC	Irrea	nce		1		rvetion	C-9 250 -80 2701m			soys			th:Syrr			000				Obsérvo	lions	1 [Ass			şih Sy)ooun						
<u>11</u>	(1) (1)	5 6	28 78	9 1				14	15			16		1	2			9.5%	28	<u>6</u>	₩1 10	(A 160	2 1 1 2 1 1	n (CS) T 14	First 5	16		12		<u>) (i</u>	43 6		្រំ	Rx1 (11 AL	¥.9	Coior	(at		Servo	
ļ				1	Í	Í	ſ		1	í							T	0		ļ	53 5		-1-		[····· ··· ··· ··· ··· ················		1 1		2	3 0	Ĭ.		10	1 +2	13	14	15		16	
				ľ	"	5		r () 251	۶ <u>۲</u>	VET	82 1 , 0	xeq, 133.	-rv4					1024 1635		- 1	51	•	a 	y ,				5	002 00	∞ <u>∞</u>	- 203	, Z	5						2(92-20	27m Pj	pt-s
				1					1										•••	1	Ŷ2	1	3 3	y [t 9]					+	-}}				701 ¹		12	J E:		Vasia S)-01	
																		126	專	50	54		¥.	1941 194		4080-1082a: ±N,	cal cly		w'œ	800 (4										
					-	1			1									133	臣				57 157 14		5.0			{ }-{		-	- 21	•	1							• • •	•••
																		1122 1725			54 60	= -		- 51	1	19-00 A		5	006 ¹ 00	(2) (0)	3].								
																		1-53	<u>}</u>			-1-		-							-	V							2442	rsy Py	
			•••	65														173		ŀ		·	3 			A1 (Sa-55-02).		5	00E 00	: co,	-		1				Í				
		20	- }							- .								120 :X.a	ļ	<u>.</u>	1521	<u> </u>	<u>.</u>	1 6 1				┤╏┤			8	ð É				- - -	-		Cer to		
										ĺ						Í			6.3	- [·	A1 10:1		1	1		A.4 (Co - S5 · Sk)		5	0C3 04	04 OC1	4	1	1_	(Su)	51		ye!		220 5-22 2232-22	E= P,	, per
																		35	т <u></u> 		<i>Q</i> 2		4 P		<u>†</u>			1 -		+		Ķ	65						-		
		1		1		1				[1										5	60490	200			1	201	51 Cy	5	yei	C14			
		- 30 3 :		· _ .										-				38		35		=	5		 		····-			- -		۰Ż		.							
					~ *	•	: ^	41 1-31	0.5	^{≯ C-3}		Fice (1 13 Fa 5, 20	. อว่ - ห่					1380 1380			07 07		<u>y P</u>	1 -	F	1		,	003 O	2,004	·32 23	¥		-		1			0 sq 91.		• • •
										332-0			luta Pe					135	•••	ŀ	Q1			1 41 101		Yey 5:1. #155	· _									1.	1		0페 에	6-93 - 2	- gre
			()	ಟ್ ಸ						}									1.3	ъ	¥1	ſ	۲ 	12			~	,	004 61	01,00	3										
• •		- 47					-		.	· · -	·						. 	140	ГŢŊ		¥1.		y	 }-	/	Yer st. resi	a				- 24	Ź	4 50						14-15 m 1353-240	-	
																				55"]		5	œ⊲œ			ĺ.							633-24	54:44	. 58.
																		:e:			00 1531	-†-	n,	, n		Rossier, Igd erg	steriet					V	1			Í	[]	ÍÍ			
								ļ	ļ												89	-1-	- Pj		Ļ	9 515 . E. ogs - 904	e por se	5	205,00		tr	ĺ.			l						
		· 50		••••														8	Ð		5		v [J.r	r, cal	.818:5034:.E.	98.110:20 x	1 1 1					1								
				Ì			ļ	ļ											٦.		Ka	ž	3	11		532-1537p, 54	-1-			æ _	, 5	\$-7	1 65	57	C)	1 3	1	1-1			
		557 Sec	1 1	55	<u> </u>			12	-	537-6	355. 1	\$ iCe.Os-	S4.SU		1			e		ł	4		-		54	ſ					-			por		1	-				
		¥1			5			6										1520	Ξ.	1	i¥.) 	<u>-</u> -	- 	╞	 	862-1566a; F.						É	1 60	301	-	13					
		- 63		ବ 	• .		2	11		fgt- :								 	11 1.1						-					(2) - 	5		4	993	_ -		 	-			
		<u>د</u> ور		55														6 4 7	•••	40 47			_	-i	i—	W32, Q2 15					75			P, O		1	*	•	- Kessine - i	rj-Oz-	
		6.5			-			1.955		Yey	lət, c	ing, tge-	- y1					64 5			<u>_</u>	_[) e 7	I	¥≱, ney keri		111				1			Į]]			
																		5 4 5		ŀ		_		_!	£	W26-728		Î	o3i⊙	× -		Ľ									
	.	10	[]																• • • •				1_	*		Py 612 655-6350; 01						1		7-04		6	75		(34 Py) 2553-270		
				53							203 m 7	5 90%A							ŗ.j		4.9	5	7 Pj	1	Ì						- 27	<u>بر نا</u> ه	1			· †					
				Ĩ																					I																
		Π.			_ _	_ _															<u>67</u>	212 1		i	I	Py Cis is store									1	ĺ					
		343 541		-1				11	/		55 g-2	۰a ۱۹۰۰														51 8 47 576															
			•	ľ				1-31 1-31	,	Yes	a	ing fat Pa ne s		*-			1	1		[- f			1						- 24	o¦	+			·					
													~~~			ĺ			•••								¢a-Fa									1					
				⊴.	1		ſ	ļ						-			1	2			51			1.1.2	3	4:5s1	\$1 - F#														
					ļ	ļ								53	508 <b>'</b> 0	03 ¦00	×! •				44 190	Fa [g	y Pi			1870-1875a : c) 1891-1855a : cy	7.							li							
		5		···   ·	Ĩ		-	-1		••••			• • • • • •	-			- -	190					<u>.</u>			A4 (M3 1914-1915a : 5p	. 0.3				23	»	<b>.</b>		<b>¦</b>	- <b> </b>		<b>  </b>			- · - <b>-</b>
						1							]	53	60	מציי			1.1				Í			1942-1945a: Cy						<b> </b> .									
								1								+		949 959		ನ ಟ		<u>-</u> [:	10	<u>, n</u>		Lorin (existed							]								
								ĺ				r is neca		v	0.32	-02 of			13		1	1	"	۲ <i>۲</i>	1	The off strend	8 CM.	11				ļĮ.	1.								




LEGEND and ABBREVIATION

í


		_	
10 Each	Pettle, sold city	Feb [	
	SUASSE	Ss [	
	Stofe	SA [	
	Mort .	Vi [	1, CL
	Lines's e	LS (	1111
	Dokumitie Timestorie	Do-Ls 🤅	1414
	Constra	Co Î	
	Siferite	S4	
	Quartz te	(n 1	
	Ore, Ligh grede		10.00
	Or, ka gote	i	
	Parite ore	- ਇਸ	7.7
	Percile at	- Han - 1	77.7
	934	St I	
	Baccic'ed rock	8-0	
	Allered mot		
	Foot, heating		<u> </u>
	* LGJ, * LC+2+E	, r	
II. Oličejka -	ci 5 ze 1	<b>c</b> •1	
	trocted	60) 163	
12 Atestion	60001120000	හ	
	050720-0	f 33	
	0/2721146	¢j	
	S"C"CO'M	\$-1	
	SECUTIVES	\$#F	•
13 Viestation:	Pyle Pr	Ociciente	(s
	B-zieus D	Occore	à
	Ze-E-e-c's Ze	Receive	Es Se
	Orde Frees Od	Yegrette	¥:
H. Ceter:	1951 I-	Nock	13
	6.72 6-		
-	93) 91	treas	1/4
5. fictore:	feit	F	
	5 6.763	\$*4	
	breteit es	t-c	
6 Observations	esseration	ē ss	
	16:55	5 5	
	12'4'4'5	v's	






ter de la companya de la companya de la companya de la companya de la companya de la companya de la companya d

Ņ




:


at i





.

64












Rock 1	Febbe, sod.	ce,	£85	(T.T.)
	Service		\$s	
	Sele		51	100.00
	No.4		¥1	
	Lissore		L.	
	Debate La	1520	Op-Es	
	Delestare		00	ΠŤ Π
	S de la		54	È₩
	Quertz te		Q*1	
	Ge, E & 6	rađe -		i
	Ce. los e			
	Prite are		£1	
	Perchite ore		85	<b></b>
	5100		9	<b>H</b>
	Breceiet an	c it	Bre	
	Altered rock		K.CO	
	Stetted ave		54	F===
	Fort		F	
	Fratae cos	ie 1		~
	Eess su	<b>6</b> 1	•	~
				· •
A'reation .	6:0012:50		60	
	(G'( \$ 25° OL		(đ	
	6.3.3522.03		c' <b>y</b>	
	stoteta sekitketa		51	
	587619-26160		541	
M e. a. 23-03	Prote	Py	Vorette	Mi
	65e-0	6	HE STOP	Hn So
	Schuterite	5ş	Occasie	Cc
	Ostayet	Q.	Lecone	Lia
	Ownitz	C1	Orice site	a's Out
	Coole	Coi		
Ceter	2 cA1	<b>I</b> -	tion.	NT.
	691	4-	1.5.2	* 4
	\$-1J	\$° J	b:+3	<b>1</b> <**
C:ter	tre-g-s-es	751	164	
	res a veces	e gi	a e coel	- 1
	COURT-9-2-24	1 445	Asses N.F.	⊳A diss
	* 'e: (C'e'e'	<b>4</b> 4	Anerst se	K1
Sziging keste	a er-f essty r	ts:1	<b>\-</b>	N - 01





Reck	FLOR, STA. CO		F25	i • • • •
	Schedione Shale Mini Liostone Octomble Exercise Octobre Sidelite One, Right grade One, Right grade One, Right grade Physic and Periodice and Periodice and Stara		S 5	
			55	
			MI	क्ति
			L S	
			Dorls	77
			Co	100
			54	2.22
			C+2	
			••	1000
			~	
			Pj 	
			Ба	1.12
			St	
	Erecticies rack		8-c	
	Allered excl		Alco.	
	Steared zone		S-4	
	Ecs'1		F	
	Fracture and	je al	3	~
•	Eesting			<b>T</b> 2
A 25 64	00-60-12-2-04		60	
	(° ( ) 2. O		cel	
	STR Data for		c'j	
	stof estea		\$1	
	Ser e fizci ca		541	
Manager	Priste	e,	<b>M4</b>	
	6-5e-1	G	Vogret te Peticite	₩1 Hos S _P e
	Spaceste	So.	Choicec te	- nu syc (c
	Decayite	Ğ	Leave	Lia
	9:01	G.	Cite File :	
	Croce	Cel		
Celer				
CC-CF.	Fgh1 671	1-	Not	21
	63L 5'ts	<b>+</b>	a bie	- 1 ⁴ 6
	¥4)	41	b:	<b>k</b> •
Giter	fre-points	f 24	12.9	
	res-averes		32.21	-
	6-0-12-00-15		& sseninc fra	
	terce'e !	<b>E</b> .4	Alecton	At
Sampling location and essay result			\~ -·N	r-01



÷ 4

